

## DC-20GHz Reflective SPDT Switch

### GaAs Monolithic Microwave IC


*new*

### Description

The CHS5100 is a wideband monolithic FET based reflective switch manufactured on a standard power process using  $0.7\mu\text{m}$  implanted active layer MESFET, via holes, air bridges and electron beam gate lithography.

This wideband switch is suitable for ultra broadband ECM and EW systems. It can also be used in instrumentation and wideband signal processing applications.

Available in chip form



### Main Features

- ☑ Broadband performance : DC-20GHz
- ☑ Low insertion loss : 2.1dB@20GHz
- ☑ High isolation : 53dB@1GHz  
30dB@20GHz
- ☑ Excellent input and output matching:  
VSWR < 1.5:1
- ☑ Chip size : 1,92 x 1,22 x 0.1mm

### Main Characteristics

Tamb = +25°C

| Symbol | Parameter               | Min | Typ | Max | Unit |
|--------|-------------------------|-----|-----|-----|------|
| II     | On state insertion loss |     |     | 2.5 | dB   |

Ref. : DSCHS51006354

1/9Er  
reur!  
Docu  
ment  
princ  
ipal  
seule  
ment

Specifications subject to change without notice

|      |                           |    |  |       |    |
|------|---------------------------|----|--|-------|----|
| Is   | Off state isolation       | 25 |  |       | dB |
| VSWR | Input and output matching |    |  | 1.5:1 |    |

ESD Protections : Electrostatic sensitive discharge device observe handling precautions !

**Electrical Characteristics**

Tamb = +25°C, specifications are given for typical control voltages and for 50ohm source and load impedance.

| Symbol           | Parameter                   | Test Conditions                         | Min | Typ                                  | Max   | Unit |
|------------------|-----------------------------|---|-----|--------------------------------------|-------|------|
| Fop              | Operating frequency range   |   | 0.5 |                                      | 20    | GHz  |
| Il               | On state insertion loss     | 1GHz<br>5GHz<br>10GHz<br>15GHz<br>20GHz |     | 1.15<br>1.20<br>1.40<br>1.60<br>2.10 | 2.50  | dB   |
| Is               | Off state reverse isolation | 1GHz<br>5GHz<br>10GHz<br>15GHz<br>20GHz | 25  | 53<br>42<br>37<br>34<br>30           |       | dB   |
| VSWR             | Input VSWR                  |   |     |                                      | 1.5:1 |      |
| VSWR             | Ouput VSWR                  |   |     |                                      | 1.5:1 |      |
| P <sub>1dB</sub> | Input compressed power      | 20GHz                                   |     | 20                                   |       | dBm  |
| Ic               | Control current             |   |     |                                      | 100   | μA   |
| VH               | High level control voltage  |   | -2  | 0                                    |       | Volt |
| VL               | Low level control voltage   |   |     | -6                                   | -4.75 | Volt |

**Absolute Maximum Ratings (1)**

Tamb = +25°C

| Symbol | Parameter                              | Value       | Unit |
|--------|--|-------------|------|
| VH,VL  | Control voltages                       | -8 to 0     | Volt |
| Pin    | Maximum peak input power overdrive (2) | 30          | dBm  |
| Top    | Operating temperature range            | -40 to +85  | °C   |
| Tstg   | Storage temperature range              | -55 to +125 | °C   |

(1) Operation of this device above anyone of these parameters may cause permanent damage

(2) Duration < 1s

## Typical Scattering Parameters

Tamb = +25°C, Bias Conditions : VL = -6V, VH = 0V, on-state IN-Out1 path

| Freq.<br>GHz | S11<br>dB | S11<br>/° | S12<br>dB | S12<br>/° | S21<br>dB | S21<br>/° | S22<br>dB | S22<br>/° |
|--------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| 0.50         | -19.93    | -4.0      | -1.10     | -5.6      | -1.11     | -5.6      | -19.98    | -5.8      |
| 1.00         | -19.85    | -11.9     | -1.12     | -10.3     | -1.13     | -10.3     | -19.88    | -15.7     |
| 1.50         | -19.73    | -19.5     | -1.14     | -15.2     | -1.14     | -15.2     | -19.75    | -25.1     |
| 2.00         | -19.63    | -26.6     | -1.15     | -20.1     | -1.15     | -20.1     | -19.60    | -33.4     |
| 2.50         | -19.59    | -33.4     | -1.17     | -25.0     | -1.17     | -25.0     | -19.41    | -42.0     |
| 3.00         | -19.46    | -39.7     | -1.18     | -29.9     | -1.19     | -29.9     | -19.27    | -50.1     |
| 3.50         | -19.38    | -46.0     | -1.19     | -34.8     | -1.20     | -34.8     | -19.08    | -58.0     |
| 4.00         | -19.27    | -52.0     | -1.21     | -39.8     | -1.21     | -39.7     | -18.91    | -65.0     |
| 4.50         | -19.21    | -57.8     | -1.23     | -44.7     | -1.23     | -44.7     | -18.74    | -72.6     |
| 5.00         | -19.22    | -62.4     | -1.25     | -49.6     | -1.25     | -49.6     | -18.62    | -78.5     |
| 5.50         | -19.05    | -67.7     | -1.26     | -54.5     | -1.26     | -54.6     | -18.45    | -85.2     |
| 6.00         | -19.02    | -72.0     | -1.28     | -59.5     | -1.28     | -59.5     | -18.45    | -90.5     |
| 6.50         | -18.96    | -75.5     | -1.30     | -64.4     | -1.30     | -64.4     | -18.35    | -95.8     |
| 7.00         | -18.59    | -88.0     | -1.31     | -69.6     | -1.31     | -69.6     | -18.01    | -109.3    |
| 7.50         | -18.61    | -92.8     | -1.33     | -74.5     | -1.33     | -74.6     | -17.84    | -115.5    |
| 8.00         | -18.52    | -96.7     | -1.34     | -79.5     | -1.35     | -79.6     | -17.92    | -121.1    |
| 8.50         | -18.56    | -101.6    | -1.36     | -84.6     | -1.36     | -84.6     | -17.76    | -127.2    |
| 9.00         | -18.50    | -104.7    | -1.38     | -89.6     | -1.38     | -89.6     | -17.83    | -132.3    |
| 9.50         | -18.51    | -109.3    | -1.40     | -94.7     | -1.40     | -94.7     | -17.82    | -138.3    |
| 10.00        | -18.56    | -112.4    | -1.42     | -99.8     | -1.42     | -99.8     | -18.04    | -143.2    |
| 10.50        | -18.59    | -115.7    | -1.45     | -104.9    | -1.44     | -104.9    | -18.05    | -149.0    |
| 11.00        | -18.69    | -119.2    | -1.46     | -110.1    | -1.46     | -110.1    | -18.22    | -153.3    |
| 11.50        | -18.67    | -122.1    | -1.48     | -115.2    | -1.48     | -115.3    | -18.29    | -158.7    |
| 12.00        | -18.83    | -124.5    | -1.50     | -120.5    | -1.50     | -120.5    | -18.52    | -162.7    |
| 12.50        | -18.95    | -127.1    | -1.52     | -125.7    | -1.52     | -125.7    | -18.68    | -167.4    |
| 13.00        | -18.97    | -130.0    | -1.54     | -131.0    | -1.55     | -131.1    | -19.01    | -171.5    |
| 13.50        | -19.12    | -132.8    | -1.57     | -136.4    | -1.57     | -136.4    | -19.21    | -175.7    |
| 14.00        | -19.19    | -134.6    | -1.58     | -141.8    | -1.59     | -141.8    | -19.63    | -179.8    |
| 14.50        | -19.33    | -136.9    | -1.60     | -147.2    | -1.60     | -147.3    | -20.01    | -175.2    |
| 15.00        | -19.54    | -139.0    | -1.63     | -152.7    | -1.63     | -152.7    | -20.18    | -172.7    |
| 15.50        | -19.67    | -141.7    | -1.66     | -158.2    | -1.66     | -158.2    | -20.59    | -166.4    |
| 16.00        | -19.73    | -143.1    | -1.68     | -163.8    | -1.68     | -163.8    | -20.97    | -163.5    |
| 16.50        | -20.17    | -145.3    | -1.71     | -169.5    | -1.71     | -169.5    | 21.10     | -160.4    |
| 17.00        | -20.44    | -148.3    | -1.75     | -175.3    | -1.75     | -175.3    | -21.89    | -154.9    |
| 17.50        | -20.80    | -149.5    | -1.78     | -179.0    | -1.78     | -178.9    | -21.89    | -151.5    |
| 18.00        | -21.11    | -154.0    | -1.82     | -173.0    | -1.82     | -173.0    | -22.51    | -147.0    |
| 18.50        | -21.78    | -156.3    | -1.86     | -167.1    | -1.86     | -167.1    | -23.39    | -140.1    |
| 19.00        | -22.61    | -159.3    | -1.91     | -161.1    | -1.91     | -161.0    | -22.64    | -126.9    |
| 19.50        | -24.05    | -164.4    | -1.95     | -155.1    | -1.95     | -155.0    | -22.32    | -125.9    |
| 20.00        | -25.54    | -162.9    | -1.98     | -148.8    | -1.98     | -148.7    | -23.99    | -122.6    |
| 20.50        | -29.33    | -165.4    | -2.02     | -142.3    | -2.03     | -142.3    | -23.53    | -99.0     |
| 21.00        | -33.39    | -164.3    | -2.07     | -135.7    | -2.08     | -135.7    | -22.77    | -89.5     |
| 21.50        | -46.45    | -92.3     | -2.13     | -129.1    | -2.13     | -129.0    | -23.50    | -92.1     |
| 22.00        | -32.38    | -30.2     | -2.21     | -122.3    | -2.21     | -122.2    | -22.97    | -61.6     |
| 22.50        | -26.53    | -20.4     | -2.30     | -115.0    | -2.31     | -115.0    | -20.57    | -52.6     |
| 23.00        | -22.06    | -23.9     | -2.44     | -107.6    | -2.44     | -107.6    | -19.13    | -47.1     |
| 23.50        | -19.35    | -29.7     | -2.62     | -100.5    | -2.63     | -100.4    | -18.64    | -27.7     |
| 24.00        | -16.65    | -34.4     | -2.78     | -93.1     | -2.79     | -93.1     | -17.00    | -15.9     |
| 24.50        | -14.54    | -39.5     | -2.98     | -85.5     | -2.97     | -85.6     | -15.65    | -6.2      |
| 25.00        | -12.84    | -45.9     | -3.21     | -78.0     | -3.21     | -77.9     | -14.67    | -6.7      |
| 25.50        | -11.32    | -51.7     | -3.45     | -70.2     | -3.45     | -70.2     | -13.41    | -16.0     |



## Typical Scattering Parameters


Tamb = +25°C, Bias Conditions : VL = -6V, VH = 0V, off-state IN-Out1 path

| Freq.<br>GHz | S11<br>dB | S11<br>/° | S12<br>dB | S12<br>/° | S21<br>dB | S21<br>/° | S22<br>dB | S22<br>/° |
|--------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| 0.50         | -18.28    | 2.8       | -60.07    | 100.4     | -62.13    | 82.9      | -1.64     | 177.1     |
| 1.00         | -17.46    | -6.1      | -52.95    | 85.5      | -54.18    | 79.4      | -1.66     | 175.3     |
| 1.50         | -18.42    | -30.5     | -50.17    | 78.2      | -49.95    | 76.6      | -1.70     | 173.4     |
| 2.00         | -17.00    | -33.7     | -47.30    | 71.7      | -47.23    | 71.4      | -1.74     | 171.4     |
| 2.50         | -18.65    | -43.5     | -45.64    | 71.5      | -45.87    | 67.7      | -1.80     | 169.6     |
| 3.00         | -19.40    | -39.9     | -44.56    | 63.7      | -44.59    | 65.9      | -1.85     | 167.7     |
| 3.50         | -16.10    | -53.3     | -43.57    | 59.8      | -43.48    | 61.0      | -1.90     | 166.0     |
| 4.00         | -17.52    | -65.5     | -42.76    | 54.3      | -42.72    | 56.3      | -1.95     | 164.1     |
| 4.50         | -20.00    | -85.2     | -41.88    | 53.2      | -41.87    | 51.5      | -1.99     | 162.6     |
| 5.00         | -18.14    | -70.0     | -40.89    | 50.3      | -41.19    | 50.4      | -2.05     | 160.8     |
| 5.50         | -19.42    | -83.4     | -40.66    | 47.2      | -40.67    | 47.4      | -2.10     | 159.3     |
| 6.00         | -18.43    | -86.0     | -40.18    | 44.0      | -40.16    | 44.2      | -2.14     | 157.5     |
| 6.50         | -17.59    | -76.1     | -39.40    | 41.9      | -39.44    | 42.2      | -2.18     | 156.1     |
| 7.00         | -18.33    | -108.9    | -39.34    | 39.4      | -39.53    | 39.6      | -2.17     | 153.9     |
| 7.50         | -17.68    | -115.8    | -39.09    | 37.6      | -38.91    | 36.0      | -2.20     | 152.4     |
| 8.00         | -22.95    | -97.1     | -38.53    | 38.5      | -38.79    | 37.6      | -2.23     | 150.6     |
| 8.50         | -20.38    | -105.2    | -38.31    | 35.6      | -38.16    | 34.2      | -2.26     | 149.2     |
| 9.00         | -17.48    | -107.6    | -37.71    | 32.3      | -37.69    | 31.3      | -2.29     | 147.5     |
| 9.50         | -18.61    | -116.2    | -37.41    | 31.1      | -37.43    | 30.3      | -2.30     | 145.9     |
| 10.00        | -20.56    | -116.4    | -37.08    | 29.7      | -37.13    | 28.4      | -2.34     | 144.1     |
| 10.50        | -18.57    | -111.6    | -36.76    | 27.3      | -36.83    | 27.3      | -2.35     | 142.6     |
| 11.00        | -16.32    | -119.9    | -36.27    | 25.9      | -36.23    | 25.1      | -2.38     | 141.0     |
| 11.50        | -18.80    | -130.9    | -36.24    | 23.4      | -36.26    | 22.2      | -2.37     | 139.4     |
| 12.00        | -16.65    | -135.8    | -35.73    | 21.5      | -35.69    | 20.4      | -2.40     | 137.8     |
| 12.50        | -18.34    | -147.2    | -35.60    | 18.8      | -35.68    | 19.7      | -2.42     | 136.2     |
| 13.00        | -23.83    | -126.4    | -35.47    | 19.6      | -35.38    | 19.6      | -2.44     | 134.6     |
| 13.50        | -14.94    | -132.1    | -34.53    | 16.4      | -34.62    | 16.6      | -2.46     | 133.0     |
| 14.00        | -17.12    | -166.8    | -34.51    | 14.1      | -34.74    | 12.5      | -2.49     | 131.4     |
| 14.50        | -17.13    | 176.4     | -34.60    | 13.8      | -34.74    | 15.3      | -2.48     | 129.5     |
| 15.00        | -16.70    | -131.4    | -33.60    | 12.2      | -33.74    | 12.0      | -2.52     | 128.1     |
| 15.50        | -17.75    | -157.7    | -33.51    | 8.6       | -33.71    | 10.0      | -2.51     | 126.3     |
| 16.00        | -18.49    | 177.3     | -33.18    | 4.5       | -33.24    | 6.1       | -2.54     | 124.8     |
| 16.50        | -19.10    | -177.5    | -32.91    | 5.2       | -32.66    | 3.7       | -2.52     | 123.3     |
| 17.00        | -37.58    | 165.7     | -33.06    | 4.1       | -32.88    | 4.4       | -2.58     | 121.3     |
| 17.50        | -21.78    | -133.6    | -32.09    | 3.4       | -32.26    | 3.6       | -2.59     | 119.9     |
| 18.00        | -15.61    | -168.0    | -31.17    | -2.6      | -31.45    | -2.6      | -2.63     | 118.0     |
| 18.50        | -21.68    | 113.7     | -31.92    | -6.6      | -32.08    | -7.0      | -2.69     | 116.3     |
| 19.00        | -42.95    | 175.9     | -31.66    | -4.9      | -31.49    | -4.6      | -2.61     | 114.5     |
| 19.50        | -27.64    | -149.1    | -31.10    | -6.7      | -31.03    | -6.1      | -2.61     | 113.6     |
| 20.00        | -26.13    | -24.4     | -31.31    | -7.2      | -31.09    | -7.5      | -2.72     | 112.4     |
| 20.50        | -21.30    | -124.6    | -30.11    | -6.6      | -30.11    | -6.8      | -2.68     | 109.3     |
| 21.00        | -23.02    | -162.6    | -29.61    | -8.0      | -29.61    | -7.6      | -2.59     | 107.8     |
| 21.50        | -26.02    | 54.4      | -28.43    | -7.5      | -28.39    | -7.6      | -2.61     | 107.3     |
| 22.00        | -30.85    | -11.7     | -26.93    | -15.9     | -26.97    | -16.0     | -2.82     | 104.3     |
| 22.50        | -23.81    | -46.8     | -26.54    | -23.0     | -26.51    | -22.8     | -2.71     | 102.0     |
| 23.00        | -20.26    | -8.9      | -26.28    | -30.3     | -26.28    | -31.0     | -2.65     | 100.2     |
| 23.50        | -19.14    | -64.5     | -25.11    | -31.2     | -25.03    | -31.1     | -3.00     | 99.2      |
| 24.00        | -21.68    | -36.9     | -24.32    | -45.3     | -24.34    | -45.2     | -2.96     | 97.8      |
| 24.50        | -14.51    | -18.5     | -24.33    | -58.0     | -24.31    | -57.9     | -2.93     | 96.1      |
| 25.00        | -14.74    | -45.9     | -24.38    | -63.4     | -24.39    | -63.2     | -3.02     | 95.2      |
| 25.50        | -11.78    | -45.7     | -24.82    | -74.5     | -24.87    | -74.1     | -3.05     | 93.6      |

## Typical on Wafer [S] Parameters

Tamb = +25°C, Bias Conditions : VL= -6V, VH = 0V






**Switch truth table (complementary logic)**

| V1   | V2   | IN to Out1 | IN to Out2 |
|------|------|------------|------------|
| Low  | High | On         | Off        |
| High | Low  | Off        | On         |

## Chip Mechanical Data



| Dimensions ( $\mu\text{m}$ ) |      |             |
|------------------------------|------|-------------|
| +10                          |      | +10         |
| 1920                         | -100 | x 1220 -100 |
|                              | +10  |             |
| Thickness :                  | 100  | -10         |
| HF pads :                    | 120  | x 80        |
| DC pads :                    | 100  | x 100       |



## Ordering Information

Chip form: CHS5100-99F/00

Information furnished is believed to be accurate and reliable. However **United Monolithic Semiconductors S.A.S.** assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of **United Monolithic Semiconductors S.A.S.** Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. **United Monolithic Semiconductors S.A.S.** products are not authorised for use as critical components in life support devices or systems without express written approval from **United Monolithic Semiconductors S.A.S.**