


QFP-ep

Exposed Pad Quad Flat Pack

- 7 x 7mm to 24 x 24mm body sizes
- 32 to 216 lead count
- Lead pitch range from 0.80mm to 0.40mm



FEATURES

- Body Sizes: 7 x 7mm to 24 x 24mm
- Package Height: 1.0mm (TQFP-ep) and 1.4mm (LQFP-ep)
- Lead Counts: 32L to 216L
- Lead Pitch: 0.40mm to 0.80mm
- Wide range of open tool leadframe and die pad sizes available
- JEDEC standard compliant
- Lead-free and Green material sets available

APPLICATIONS

- ASIC
- DSP
- Gate Array
- Logic, Microprocessors/Controllers
- Multimedia, PC Chipsets, Others

DESCRIPTION

STATS ChipPAC's Exposed Pad Quad Flat Pack (QFP-ep) is a thermally enhanced version of the QFP package. Thermal enhancement is achieved by means of an exposed die pad, which can be soldered to a mother PC board for effective heat removal and grounding. STATS ChipPAC's QFP-ep family includes the Exposed Pad-Low Profile QFP (LQFP-ep) and the Exposed Pad-Thin QFP (TQFP-ep). These enhanced thermal packages are made possible by deep downset die pad leadframe design combined with well controlled low loop wirebonding and package warpage control during the molding process.

QFP-ep

Exposed Pad Quad Flat Pack

SPECIFICATIONS

Die Thickness	304-482 μ m (12-19mils) range preferred
Gold Wire	25/30 μ m (1.0/1.2mils) diameter, 99.999% Au
Lead Finish	85/15 Sn/Pb or Matte Tin
Marking	Laser/ink
Packing Options	JEDEC tray/tape and reel

RELIABILITY

Moisture Sensitivity Level	JEDEC Level 3
Temperature Cycling	-65°C/150°C, 1000 cycles
High Temperature Storage	150°C, 500 hrs
Pressure Cooker Test	121°C 100% RH, 2 atm, 168 hrs
Liquid Thermal Shock (opt)	-55°C/125°C, 1000 cycles

THERMAL PERFORMANCE, θ_{ja} (°C/W)

Package	Body Size (mm)	Pad Size (mm)	Die Size (mm)	PCB Vias	Thermal Performance, θ_{ja} (°C/W)
48L	7 x 7 x 1.0	5.5 x 5.5	5.3 x 5.3	25	26.9
64L	10 x 10 x 1.0	6.5 x 6.5	6.0 x 6.0	36	24.0
80L	12 x 12 x 1.0	7.2 x 7.2	6.0 x 6.0	36	23.0

Note: Simulation data for package mounted on 4 layer PCB (per JEDEC JESD51-7) under natural convection as defined in JESD51-2.


ELECTRICAL PERFORMANCE

Electrical parasitic data is highly dependent on the package layout. 3D electrical simulation can be used on the specific package design to provide the best prediction of electrical behavior. Data below is for a frequency of 100MHz and assumes 1.0 mil gold bonding wire.


Conductor Component	Length (mm)	Resistance (mOhms)	Inductance (nH)	Inductance Mutual (nH)	Capacitance (pF)	Capacitance Mutual (pF)
Wire	2	120	1.65	0.45 - 0.85	0.10	0.01 - 0.02
Lead (14 x 14mm, 100L)	4.4 - 5.9	30.5 - 41.4	1.52 - 2.07	0.70 - 0.93	0.70 - 0.95	0.39 - 0.52
Total (14 x 14mm, 100L)		150.5 - 161.4	3.17 - 3.72	1.15 - 1.78	0.8 - 1.05	0.4 - 0.54
Wire	2	120	1.65	0.45 - 0.85	0.10	0.01 - 0.02
Lead (20 x 20mm, 144L)	4.2 - 6.1	29.3 - 42.8	1.47 - 2.14	0.68 - 0.98	0.75 - 1.10	0.44 - 0.65
Total (20 x 20mm, 144L)		149.3 - 162.8	3.12 - 3.79	1.13 - 1.83	0.85 - 1.20	0.45 - 0.67

CROSS-SECTION

TQFP-ep



LQFP-ep



PACKAGE CONFIGURATIONS

	Package Size	Lead Count			
		0.80mm	0.65mm	0.50mm	0.40mm
TQFP-ep	7 x 7 x 1.0	32	-	48	-
	10 x 10 x 1.0	44, 48	52	64	-
	12 x 12 x 1.0	52	64	80	100
	14 x 14 x 1.0	64	80	100	-
LQFP-ep	10 x 10 x 1.4	-	-	64	-
	14 x 14 x 1.4	64	80	100	-
	20 x 20 x 1.4	96	128	144	164
	24 x 24 x 1.4	-	-	-	216

Corporate Office 10 Ang Mo Kio St. 65, #05-17/20 Techpoint, Singapore 569059 Tel: 65-6824-7777 Fax: 65-6720-7823

Global Offices USA 510-979-8000 JAPAN 81-43-351-3320 CHINA 86-21-5976-5858 MALAYSIA 603-4257-6222
KOREA 82-31-639-8911 TAIWAN 886-3-593-6565 UK 44-1483-413-700 NETHERLANDS 31-38-333-2023

The STATS ChipPAC logo is a registered trademark of STATS ChipPAC Ltd. All other product names and other company names herein are for identification purposes only and may be the trademarks or registered trademarks of their respective owners. STATS ChipPAC disclaims any and all rights in those marks. STATS ChipPAC makes no guarantee or warranty of its accuracy in the information given, or that the use of such information will not infringe on intellectual rights of third parties. Under no circumstances shall STATS ChipPAC be liable for any damages whatsoever arising out of the use of, or inability to use the materials in this document. STATS ChipPAC reserves the right to change the information at any time and without notice.

©Copyright 2005. STATS ChipPAC Ltd. All rights reserved.
January 2005