

Part Number: WP34SF7C


### Features

- MECHANICALLY AND SPECTRALLY MATCHED TO THE WP32P3C PHOTOTRANSISTOR.
- WATER CLEAR LENS.
- RoHS COMPLIANT.

### Description

SF7 Made with Gallium Aluminum Arsenide Infrared Emitting diodes.

### Package Dimensions



#### Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.25(0.01")$  unless otherwise noted.
3. Lead spacing is measured where the leads emerge from the package.
4. Specifications are subject to change without notice.

## Selection Guide

Part No.	Dice	Lens Type	Po (mW/sr) [2] @ 20 mA *50mA		Viewing Angle [1]
			Min.	Typ.	2θ1/2
WP34SF7C	GaAlAs	WATER CLEAR	7	18	50°
			*10	*45	

Notes:

- 1.θ1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.
- 2.\*Luminous intensity with asterisk is measured at 50mA; Radiant Intensity / luminous flux: +/-15%.

## Electrical / Optical Characteristics at TA=25°C

Item	P/N	Symbol	Typ.	Max.	Units	Test Conditions
Forward Voltage [1]	SF7	V <sub>F</sub>	1.4	1.6	V	I <sub>F</sub> =20mA
Reverse Current	SF7	I <sub>R</sub>	-	10	uA	V <sub>R</sub> =5V
Capacitance	SF7	C	30	-	pF	V <sub>F</sub> =0V;f=1MHz
Peak Spectral Wavelength	SF7	λ <sub>P</sub>	850	-	nm	I <sub>F</sub> =20mA
Spectral Bandwidth	SF7	Δλ <sub>1/2</sub>	50	-	nm	I <sub>F</sub> =20mA

Note:


1. Forward Voltage: +/-0.1V.

## Absolute Maximum Ratings at TA=25°C





Parameter	Symbol	SF7	Units
Power Dissipation	P <sub>T</sub>	80	mW
DC Forward Current	I <sub>F</sub>	50	mA
Peak Forward Current[1]	i <sub>FS</sub>	1	A
Reverse Voltage	V <sub>R</sub>	5	V
Operating Temperature	T <sub>A</sub>	-40 To +85	°C
Storage Temperature	T <sub>STG</sub>	-40 To +85	°C
Lead Solder Temperature [2]	260°C For 3 Seconds		
Lead Solder Temperature [3]	260°C For 5 Seconds		

Notes:

1. 1/100 Duty Cycle, 10μs Pulse Width.
2. 2mm below package base.
3. 5mm below package base.





## WP34SF7C



## PACKING & LABEL SPECIFICATIONS

WP34SF7C




1,000PCS / BAG




56K / 9# BOX

OUTSIDE LABEL



OUTSIDE LABEL

28K / 5# BOX

<b>Kingbright</b>				
Q.C.	<table border="1"> <tr> <td style="text-align: center;">QC</td> </tr> <tr> <td style="text-align: center;">xxx xx xxxx</td> </tr> <tr> <td style="text-align: center;">PASSED</td> </tr> </table>	QC	xxx xx xxxx	PASSED
QC				
xxx xx xxxx				
PASSED				
TYPE NO :	WP34XXX			
QUANTITY :	1,000 pcs			
S/N :	xxx			
	CODE: xx			
LOT NO :	 <small>xxxxxxxxxx</small>			
RoHS Compliant				

Date