

Inductors

Epoxy Conformal Coated, Axial Leaded



STANDARD ELECTRICAL SPECIFICATIONS						
IND. (μH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SRF MIN. (MHz)	DCR MAX. (Ohms)	RATED DC CURRENT (mA)
0.10	± 5 %, ± 10 %	25	25.2	320	0.15	1750
0.12	± 5 %, ± 10 %	25	25.2	320	0.16	1650
0.15	± 5 %, ± 10 %	25	25.2	320	0.17	1560
0.18	± 5 %, ± 10 %	25	25.2	320	0.19	1480
0.22	± 5 %, ± 10 %	25	25.2	300	0.21	1400
0.27	± 5 %, ± 10 %	25	25.2	300	0.24	1320
0.33	± 5 %, ± 10 %	25	25.2	300	0.28	1280
0.39	± 5 %, ± 10 %	25	25.2	280	0.32	1200
0.47	± 5 %, ± 10 %	25	25.2	250	0.36	1150
0.56	± 5 %, ± 10 %	25	25.2	230	0.41	1100
0.68	± 5 %, ± 10 %	25	25.2	210	0.47	1030
0.82	± 5 %, ± 10 %	45	25.2	172	0.24	980
1.0	± 5 %, ± 10 %	45	25.2	140	0.24	920
1.2	± 5 %, ± 10 %	50	7.96	140	0.27	880
1.5	± 5 %, ± 10 %	50	7.96	131	0.30	830
1.8	± 5 %, ± 10 %	55	7.96	121	0.32	790
2.2	± 5 %, ± 10 %	55	7.96	110	0.35	750
2.7	± 5 %, ± 10 %	60	7.96	100	0.35	720
3.3	± 5 %, ± 10 %	65	7.96	94	0.35	670
3.9	± 5 %, ± 10 %	65	7.96	86	0.37	640
4.7	± 5 %, ± 10 %	70	7.96	80	0.39	620
5.6	± 5 %, ± 10 %	70	7.96	74	0.43	590
6.8	± 5 %, ± 10 %	75	7.96	68	0.48	550
8.2	± 5 %, ± 10 %	70	7.96	53	0.52	530
10	± 5 %, ± 10 %	70	2.52	45	0.58	500
12	± 5 %, ± 10 %	70	2.52	34	0.63	480
15	± 5 %, ± 10 %	70	2.52	20	0.72	460
18	± 5 %, ± 10 %	65	2.52	14	0.77	430
22	± 5 %, ± 10 %	40	2.52	9.9	0.84	410
27	± 5 %, ± 10 %	55	2.52	7.6	0.94	390
33	± 5 %, ± 10 %	55	2.52	6.3	1.03	370
39	± 5 %, ± 10 %	50	2.52	6.3	1.12	350
47	± 5 %, ± 10 %	45	2.52	6.3	1.22	340
56	± 5 %, ± 10 %	40	2.52	6.2	1.34	320
68	± 5 %, ± 10 %	40	2.52	5.7	1.47	306
82	± 5 %, ± 10 %	35	2.52	5.3	1.62	290
100	± 5 %, ± 10 %	30	2.52	4.8	1.80	275
120	± 5 %, ± 10 %	70	0.796	3.8	3.7	185
150	± 5 %, ± 10 %	70	0.796	3.5	4.2	175
180	± 5 %, ± 10 %	70	0.796	3.3	4.6	165
220	± 5 %, ± 10 %	70	0.796	3.0	5.1	155
270	± 5 %, ± 10 %	65	0.796	2.8	5.8	146
330	± 5 %, ± 10 %	65	0.796	2.6	6.4	137
390	± 5 %, ± 10 %	65	0.796	2.4	7.0	133
470	± 5 %, ± 10 %	60	0.796	2.25	7.7	126
560	± 5 %, ± 10 %	60	0.796	2.10	8.5	120
680	± 5 %, ± 10 %	55	0.796	1.95	9.4	113
820	± 5 %, ± 10 %	55	0.796	1.85	12.0	100
1000	± 5 %, ± 10 %	50	0.796	1.40	17.4	100

FEATURES

- High performance ferrite core is used in this epoxy conformally coated choke which allows for inductance values to 1000 μH
- Axial lead type, small lightweight design
- Special magnetic core structure contributes to high Q and self-resonant frequencies
- Treated with epoxy resin coating for humidity resistance to ensure long life
- Heat resistant adhesives and special structural design for effective open circuit measurement



RoHS COMPLIANT

ELECTRICAL SPECIFICATIONS

Inductance Range: 0.1 μH to 1000 μH

Inductance Tolerance: ± 10 % from 0.1 μH to 1000 μH standard, ± 5 % optional

Operating Temperature Range: - 20 °C to + 105 °C

Dielectric Strength: 250 VRMS

MECHANICAL SPECIFICATIONS

Terminal Strength: Pull = 5 pounds, Twist = 360° C x 3

Protection: Epoxy uniform roll coated

Leads: Tinned copper

ENVIRONMENTAL SPECIFICATIONS

Maximum Temperature Rise: + 20 °C

DIMENSIONS in inches [millimeters]				
MODEL	A (Max.)	B (Max.)	C (Max.)	D (Max.)
IRF-36	0.236 [6.0]	0.157 [4.0]	0.551 [14.0]	0.026 [0.65]

DESCRIPTION				
IRF-36	4.7 μH	± 10 %	ER	e3
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER INFORMATION				
I R F	3 6	E R	4 R 7	K
PRODUCT FAMILY	SIZE	PACKAGE CODE	INDUCTANCE VALUE	TOL.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.