

## FEATURES AND SPECIFICATIONS



# 7.50mm (.295") Pitch 37 Series Beau® Eurostyle® Pluggable Terminal Blocks

*Beau Eurostyle 37 series provides design flexibility with a range of plug and header configurations*

**39371, 39372, 39373,  
39374**

The 37 series of pluggable terminal blocks consists of 2 headers, right angle or vertical mount, and 3 plug styles including right angle and vertical forward or vertical reverse facing.

The increased pitch size of 7.50mm (.295") offers the ability to use up to a 12 AWG wire at 15.0A. It also allows ratings of 400V, necessary in some applications.

Constructed with rising cage clamp termination technology, the 37 series meets all applicable industry standards and is footprint compatible and cross-mateable with many of our competitors.



### Features and Benefits

- High-reliability rising cage clamp connection technology ensures a gas-tight connection without strand damage
- 7.50mm (.295") increased pitch size allows for use of wire up to 12 AWG at 15.0A
- Right angle and vertical plugs and headers allow various options for wiring to meet customer needs
- Funnel entry housing provides easier wire insertion

## SPECIFICATIONS

### Reference Information

Packaging: Box  
UL File No.: E48521  
Guide No.: XCFR2  
UL for Canada File No.: E48521  
Guide No.: XCFR8 (Pending)

### Electrical

Voltage: 300V  
Current:  
12 AWG – 15.0A  
14 to 30 AWG – 12.0A  
Insulation Resistance: 1000 Megohms min.

### Mechanical

Rec. Tightening Torque: 0.40-0.60 Nm  
(3.50-5.30 in.-lbs.)  
Wire Strip Length: 6.00 to 7.50mm  
(.236 to .295")  
Wire Range: 14 to 30 AWG  
(2.08-0.05mm<sup>2</sup>)  
Operating Temperature: +110°C

### Physical

Plugs: 39371-00XX, 39374-08XX,  
39374-09XX  
Housing: Polyamide 6.6  
UL94 V-0, Black  
Terminal: Phosphor Bronze  
Screw: M3 Copper Alloy  
Cage Clamp: Copper Alloy  
Plating:  
Terminal – Tin  
Screw – Nickel  
Cage Clamp – Nickel  
Headers: 39372-00XX, 39373-00XX  
Housing: Polyamide 6.6 UL 94V-0, Black  
Pin: Phosphor Bronze  
Pin Plating: Tin

## APPLICATIONS



## 7.50mm (.295") Pitch 37 Series Beau® Eurostyle® Pluggable Terminal Blocks

- Motor controls
- Power supplies
- Actuators
- Factory automation equipment
- Elevator controls

**39371, 39372, 39373,  
39374**



## ORDERING INFORMATION

Order No.	Product Type	Orientation	Description
39371-00XX	Plug	Right Angle	
39374-08XX	Plug	Vertical	Rear Wire Entry
39374-09XX	Plug	Vertical	Front Wire Entry
39372-00XX	Header	Vertical	Closed End
39373-00XX	Header	Right Angle	Closed End

Replace XX with no. of circuits, 02 to 12.

**Americas Headquarters**  
Lisle, Illinois 60532 U.S.A.  
1-800-78MOLEX  
amerinfo@molex.com

**Far East North Headquarters**  
Yamato, Kanagawa, Japan  
81-462-65-2324  
feninfo@molex.com

**Far East South Headquarters**  
Jurong, Singapore  
65-6-268-6868  
fesinfo@molex.com

**European Headquarters**  
Munich, Germany  
49-89-413092-0  
eurinfo@molex.com

**Corporate Headquarters**  
2222 Wellington Ct.  
Lisle, IL 60532 U.S.A.  
630-969-4550  
Fax: 630-969-1352

Visit our Web site at <http://www.molex.com/products/tblocks.html>