



# SPECIFICATION FOR APPROVAL

REF : 20090825-B


PAGE: 1

PROD.	SHIELDED SMD	ABC'S DWG No.	HP1205□□□□2□-□□□
NAME	POWER INDUCTOR	ABC'S ITEM No.	

## I . MECHANICAL DIMENSIONS :





- A : 13.5 ± 0.4 m/m
- B : 12.5 ± 0.3 m/m
- C : 4.00 ± 0.3 m/m
- D : 5.00 max. m/m
- E : 2.00 ± 0.5 m/m
- F : 5.00 typ. m/m
- G : 8.00 typ. m/m
- H : 14.0 typ. m/m



( PCB Pattern )

## II . SCHEMATIC DIAGRAM :




## III . MATERIALS LIST :

- a . Core : Iron powder
- b . Wire : Enamelled copper wire
- c . Cilp : Cu / Ni / Sn
- d . Remark : Products comply with RoHS' requirements

## IV . GENERAL SPECIFICATION :

- a . Storage temp. : -55°C ~ +125°C
- b . Operating temp. : -55°C ~ +125°C  
(Temp. rise included)
- c . Resistance to solder heat : 260°C. 10 secs.

Peak Temp : 260°C max.  
 Max time above 230°C : 50sec max.  
 Max time above 200°C : 70sec max.



AR-001A

# SPECIFICATION FOR APPROVAL

REF : 20090825-B

PAGE: 2


PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG No.	HP1205□□□□2□-□□□
		ABC'S ITEM No.	

## V . ELECTRICAL CHARACTERISTICS :

DWG No.	Inductance L ( $\mu$ H )	Isat(A) typ.	Irms(A) typ.	RDC ( $m\Omega$ )	
				max.	typ.
HP1205R10M2□-□□□	0.10 $\pm$ 20 %	118.0	55.0	0.6	0.55
HP1205R22M2□-□□□	0.22 $\pm$ 20 %	110.0	51.0	0.8	0.65
HP1205R33M2□-□□□	0.33 $\pm$ 20 %	80.0	42.0	1.1	0.90
HP1205R47M2□-□□□	0.47 $\pm$ 20 %	65.0	38.0	1.3	1.10
HP1205R56M2□-□□□	0.56 $\pm$ 20 %	55.0	36.0	1.5	1.30
HP1205R68M2□-□□□	0.68 $\pm$ 20 %	54.0	34.0	1.7	1.50
HP1205R82M2□-□□□	0.82 $\pm$ 20 %	53.0	31.0	2.3	2.00
HP12051R0M2□-□□□	1.00 $\pm$ 20 %	50.0	29.0	2.5	2.30
HP12051R5M2□-□□□	1.50 $\pm$ 20 %	48.0	23.0	4.0	3.50
HP12051R8M2□-□□□	1.80 $\pm$ 20 %	40.0	19.0	5.0	4.50
HP12052R2M2□-□□□	2.20 $\pm$ 20 %	32.0	17.0	5.5	5.00
HP12053R3M2□-□□□	3.30 $\pm$ 20 %	32.0	15.0	9.0	8.00
HP12054R7M2□-□□□	4.70 $\pm$ 20 %	27.0	12.0	15.0	13.00
HP12055R6M2□-□□□	5.60 $\pm$ 20 %	22.0	11.5	16.5	14.00
HP12056R8M2□-□□□	6.80 $\pm$ 20 %	21.0	11.0	18.5	15.50
HP12057R8M2□-□□□	7.80 $\pm$ 20 %	18.0	10.0	20.5	17.50
HP12058R2M2□-□□□	8.20 $\pm$ 20 %	18.0	9.5	22.5	19.00
HP1205100M2□-□□□	10.0 $\pm$ 20 %	16.0	9.0	25.5	21.50

- 1). □ : Packaging information ...  A : Bulk     B : Taping Reel
- 2). "- □□□":Reference code
- 3). Measured frequency of inductance is 100 KHz / 0.25V
- 4). Isat base on inductance drop 20% typ. of L value at 20°C
- 5). Irms base on temp. rise 40°C typ.

AR-001A



# SPECIFICATION FOR APPROVAL



REF : 20090825-B

PAGE: 3

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG No.	HP1205□□□□2□-□□□
		ABC'S ITEM No.	

## VI . PACKAGING INFORMATION :

### ( 1 ) Configuration



### ( 2 ) Dimensions

Unit:m/m

Style	A	B	C	D	G	N	T
13 - 24	330	21±0.8	13±0.5	24	26 <sup>+0</sup>	50 <sup>-0</sup>	30.4

### ( 3 ) QTY & G.W. Per package

Series	Inner : Reel			Outer : Carton		
	QTY (pcs)	G.W. (gw)	Style	QTY (pcs)	G.W. (Kg)	Size (cm)
HP1205	700	3,400	13 - 24	2,800	15.0	40 x 40 x 24

AR-001A


# SPECIFICATION FOR APPROVAL

REF : 20090825-B

PAGE: 4

PROD. NAME	SHIELDED SMD  POWER INDUCTOR	ABC'S DWG No.  ABC'S ITEM No.	HP1205□□□□2□-□□□
---------------	------------------------------------	-------------------------------------	------------------

**VII . DWGING NUMBER EXPRESSION :**



**Appendix code 1 : Product Classification**

- L : Lead Free Standard products comply with RoHS' requirements
- 1 ~ 9 : Lead Free Special products comply with RoHS' requirements

**Appendix code 2 : Package Information**

Code	Inner package	Inner package Q'TY	Remark
A	T.B.D.	T.B.D	
B	T / R ( Reel package )	700 pcs	

# SPECIFICATION FOR APPROVAL

REF : 20090825-B

PAGE: 5

PROD. NAME	SHIELDED SMD  POWER INDUCTOR	ABC'S DWG No.  ABC'S ITEM No.	HP1205□□□□2□-□□□
---------------	------------------------------------	-------------------------------------	------------------

**VIII . RELIABILITY TEST :**

Test item	Specification	Test condition						
Solderability	More than 95% of the terminal electrode shall be covered With fresh solder.	Preconditioning: 150°C/16Hrs±30min Dry Bake Solder : Sn96.5 / Ag3 / Cu0.5 or equivalent Solder temp. :245±5°C Flux : Rosin Dip time: 5±0.5sec						
Thermal shock test ( Temp. cycle )	Electrical oharacteristics shall not change more than ±20%	<table style="width: 100%; border: none;"> <tr> <td style="text-align: center;">Room temp. 15 minutes</td> <td style="text-align: center;">→</td> <td style="text-align: center;">-55 °C 30 minutes</td> </tr> <tr> <td style="text-align: center;">Room temp. 15 minutes</td> <td style="text-align: center;">→</td> <td style="text-align: center;">+125 °C 30 minutes</td> </tr> </table> <p>Total : 50 cycles</p>	Room temp. 15 minutes	→	-55 °C 30 minutes	Room temp. 15 minutes	→	+125 °C 30 minutes
Room temp. 15 minutes	→	-55 °C 30 minutes						
Room temp. 15 minutes	→	+125 °C 30 minutes						
Humidity Test		Temperature : 40±2°C Humidity : 90±5% Time : 1000 hours						
High temp. Resistance test		Temperature : 125±5°C Applied current : Per spec. Time : 96 hours						

AR-001A



# SPECIFICATION FOR APPROVAL

REF : 20090825-B

PAGE: 6

PROD.	SHIELDED SMD	ABC'S DWG No.	HP1205□□□□2□-□□□
NAME	POWER INDUCTOR	ABC'S ITEM No.	

IX . UL CARD :

OBMW2 September 8, 2000

Magnet Wire-Component

JUNG SHING WIRE CO LTD E174837

231 CHUNG CHENG RD, SEC 3 JEN-TEH HSIANG, TAINAN

HSIEN TAIWAN

Mtl Dsg	Mark Dsg	BC	Coat Typ	OC	ANSI Type	Temp Class
AIW	---	Polyamideimide	---	---	MW81-C	220
CFUEWB	---	Polyurethane	---	---	MW75C	130
EIAIW	---	Polyesterimide	Polyamideimide	---	MW35C	200
EILOCKY	---	Polyesterimide	Polyamide	---	---	180
EILOCKW	---	Polyesterimide	Modified Epoxy	---	---	200
EIW	---	Polyesterimide	---	---	---	220
EIW-2	---	Polyesterimide	---	---	MW74-C	200
FL.EILOCKY	---	Modified Polyester	Polyamide	---	---	155
LSFFW	---	Polyurethane	---	---	MW79-C	155
LSUEW	---	Polyurethane	---	---	---	130
PEW	---	Polyester	---	---	---	155
PEY	---	Polyester	Nylon	---	MW24-C	155
SF.FLW	---	Modified Polyester	---	---	MW26C	155
SF.EIW	---	Polyesterimide	---	---	MW77C	180
SF.BY@	---	Modified Polyester	Nylon	---	MW27-C	155
SF.FLY@	---	Modified Polyester	Nylon	---	MW27-C	155
SF.BLOCKBS	---	Modified Polyester	Modified Polyamide	---	---	155
SF.EILOCKY#	---	Polyesterimide	Polyamide	---	---	180
SF.EILOCKBS	---	Polyesterimide	Modified Polyamide	---	---	180
SF.BW@	---	Modified Polyester	---	---	MW26C	155
SFFW	---	Polyurethane	---	---	MW79	155

287806002 Page 1 of 2

A not-for-profit organization  
dedicated to public safety and  
committed to quality service

Mtl Dsg	Mark Dsg	BC	Coat Typ	OC	ANSI Type	Temp Class
SFFY	---	Polyurethane	Polyamide	---	MW80C	155
UEW-1	---	Polyurethane	---	---	MW2-C	105
UEW-2	---	Polyurethane	---	---	---	130
UEW-4	---	Polyurethane	---	---	MW75C	130
UEY	---	Polyurethane	Nylon	---	MW28-C	130
UEY-2	---	Polyurethane	Polyamide	---	MW28-C	130

@-May be suffixed by LZ; # - May be suffixed by LZ, EL or LZI.  
LZ- Signifies magned wires twisted together; EL - signifies base coated magnet wire laid parallel with top coat applied overall; LZL - signi-  
fies base coated magnet wire twisted together and covered with top coat overall.

Marking: Company name or trademarks JSW or 千如電線, material designation or marked designation on packaed or reel, and  
Recognized Component Mark.

See General Information Preceding These Recognitions  
For use only in equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

287806002 Page 2 of 2

OBMW2/E174837  
September 8, 2000

AR-001A

