



① Substrate: 1.59mm \pm 0.18mm [0.0625" \pm 0.007"]
FR4/G10 or equivalent high temp material. 17 μ m [1/2 oz.] Cu clad. SnPb plating.

② Pins: material- Brass Alloy 360 1/2 hard; finish- 0.25 μ m [10 μ "] Au over 1.27 μ m [50 μ "] Ni (min.).

③ Pins: shell material- Brass Alloy 360 1/2 hard; finish- 0.25 μ m [10 μ "] Au over 1.27 μ m [50 μ "] Ni (min.). Contact material- BeCu; finish 0.25 μ m [10 μ "] Au over 2.54 μ m [100 μ "] Ni (min.).

⑤ Test points: material- Phosphor Bronze; plating- Sn over 1.27 μ m [50 μ "] Ni. Gold flash on contact end.

Description: PLCC Carrier Adaptor
84 position PLCC ZIF socket to 84 position PLCC clip with test points.

Tolerances: diameters \pm 0.03mm [\pm 0.001"], PCB perimeters \pm 0.13mm [\pm 0.005"], PCB thicknesses \pm 0.18mm [\pm 0.007"], pitches (from true position) \pm 0.08mm [\pm 0.003"], all other tolerances \pm 0.13mm [\pm 0.005"] unless stated otherwise. Materials and specifications are subject to change without notice.

	CA-PLCC84-Z-C-T-01 Dwg © 2001 IRONWOOD ELECTRONICS, INC. PO BOX 21151 ST. PAUL, MN 55121 Tele: (651) 452-8100 www.ironwoodelectronics.com	Status: Released	Scale: 1:0.75	Rev: A	
		Drawing: M. Tully		Date: 2/14/01	
		File: CA-PLCC084-Z-C-T-01 Dwg.mcd			ECO#