



18/19 LED Cluster, 15mm SC Bayonet Based Lamps

Packages	Replaces Incandescent # (Application Specific)	Part Number	Input Voltage	Power (Watts) typ	Intensity per LED I _v (mcd) typ	λ _p (nm)	View Angle 2θ _{1/2}	Optional Viewing Angles*
660nm Ultra Red GaAlAs/GaAlAs	309,311, 1383,1384, 1723, 3011	B618-0UR-014N	12/14V	1.0 to 1.7	2000	660	12° to 15°	Replace N in part number with required viewing angle S - Standard (20° to 30°) M - Medium (50° to 60°) W - Wide (120°)
		B618-0UR-024N	24V					
		B618-0UR-028N	28V					
		B619-0UR-036N	36V					
633nm Super Red InGaAlP	309,311, 1383,1384, 1723, 3011	B618-0ER-014N	12/14V	1.0 to 1.7	3500	633	12° to 15°	Replace N in part number with required viewing angle S - Standard (20° to 30°) M - Medium (50° to 60°) W - Wide (120°)
		B618-0ER-024N	24V					
		B618-0ER-028N	28V					
		B619-0ER-120AN	120VAC					
612nm Super Orange InGaAlP	309,311, 1383,1384, 1723, 3011	B618-0UO-014N	12/14V	1.0 to 1.7	6500	612	12° to 15°	Replace N in part number with required viewing angle S - Standard (20° to 30°) M - Medium (50° to 60°) W - Wide (120°)
		B618-0UO-024N	24V					
		B618-0UO-028N	28V					
		B619-0UO-120AN	120VAC					
595nm Super Yellow InGaAlP	309,311, 1383,1384, 1723, 3011	B618-0UY-014N	12/14V	1.0 to 1.7	5500	595	12° to 15°	Replace N in part number with required viewing angle S - Standard (20° to 30°) M - Medium (50° to 60°) W - Wide (120°)
		B618-0UY-024N	24V					
		B618-0UY-028N	28V					
		B619-0UY-120AN	120VAC					
4500K Incandescent White SiC/GaN	309,311, 1383,1384, 1723, 3011	B618-0IW-014N	12/14V	1.0 to 1.7	2000	4500K	12° to 15°	Replace N in part number with required viewing angle S - Standard (20° to 30°) M - Medium (50° to 60°) W - Wide (120°)
		B618-0IW-024N	24V					
		B618-0IW-028N	28V					
		B619-0IW-120AN	120VAC					
8000K Cool White SiC/GaN	309,311, 1383,1384, 1723, 3011	B618-0CW-014N	12/14V	1.0 to 1.7	6000	8000K	12° to 15°	Replace N in part number with required viewing angle S - Standard (20° to 30°) M - Medium (50° to 60°) W - Wide (120°)
		B618-0CW-024N	24V					
		B618-0CW-028N	28V					
		B619-0CW-120AN	120VAC					
570nm Lime Green InGaAlP	309,311, 1383,1384, 1723, 3011	B618-0UG-014N	12/14V	1.0 to 1.7	1000	570	12° to 15°	Replace N in part number with required viewing angle S - Standard (20° to 30°) M - Medium (50° to 60°) W - Wide (120°)
		B618-0UG-024N	24V					
		B618-0UG-028N	28V					
		B619-0UG-120AN	120VAC					
525nm Aqua Green SiC/GaN	309,311, 1383,1384, 1723, 3011	B618-0AG-014N	12/14V	1.0 to 1.7	10,000	525	12° to 15°	Replace N in part number with required viewing angle S - Standard (20° to 30°) M - Medium (50° to 60°) W - Wide (120°)
		B618-0AG-024N	24V					
		B618-0AG-028N	28V					
		B619-0AG-120AN	120VAC					
505nm Blue Green SiC/GaN	309,311, 1383,1384, 1723, 3011	B618-0BG-014N	12/14V	1.0 to 1.7	2000	505	12° to 15°	Replace N in part number with required viewing angle S - Standard (20° to 30°) M - Medium (50° to 60°) W - Wide (120°)
		B618-0BG-024N	24V					
		B618-0BG-028N	28V					
		B619-0BG-120AN	120VAC					
470nm Super Blue SiC/GaN	309,311, 1383,1384, 1723, 3011	B618-0PB-014N	12/14V	1.0 to 1.7	3000	470	12° to 15°	Replace N in part number with required viewing angle S - Standard (20° to 30°) M - Medium (50° to 60°) W - Wide (120°)
		B618-0PB-024N	24V					
		B618-0PB-028N	28V					
		B619-0PB-120AN	120VAC					

Viewing Angle: 12° to 15°



Narrow Angle (N)


Optional Viewing Angles: 20° to 30°



Standard Angle (S)



Medium Angle (M)




Wide Angle (W)

***Notes:**


- Not all possible combinations of voltage, intensity and angle are available
- Intensity shown is for narrow angle (N). Intensity is reduced 12 to 15 times when using extra wide angles

InfraReds

850/880/940nm




Dimensions



Low Cost Specials: (for qualified applications)

- 8000K Cool White PN Example: B618-1CW-120AN
- 525nm Aqua Green PN Example: B618-1AG-120AN
- 505nm Blue Green PN Example: B618-1BG-120AN
- 470nm Super Blue PN Example: B618-1PB-120AN



Custom Options: (for qualified applications)

Baseless with 12" wire leads

Series: L618/L619

PN Example: L618-0UO-014N

Specifications subject to change without notice.

• All Lamps are Bipolar (AC & DC Compatible)

• Three-Year Lamp Warranty

LEDTRONICS, INC.
THE FUTURE OF LIGHT



23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579-4875 or (310) 534-1505
Fax: (310) 534-1424
E-mail: webmaster@ledtronics.com
Website: www.ledtronics.com

Log # 123C Rev 12-2000