


## **KSC1623**

# Low Frequency Amplifier & High Frequency OSC.

• Complement to KSA812



1. Base 2. Emitter 3. Collector

## **NPN Epitaxial Silicon Transistor**

## **Absolute Maximum Ratings** $T_a$ =25°C unless otherwise noted


Symbol	Parameter	Ratings	Units
V <sub>CBO</sub>	Collector-Base Voltage	60	V
V <sub>CEO</sub>	Collector-Emitter Voltage	50	V
V <sub>EBO</sub>	Emitter-Base Voltage	5	V
I <sub>C</sub>	Collector Current	100	mA
P <sub>C</sub>	Collector Power Dissipation	200	mW
T <sub>J</sub>	Junction Temperature	150	°C
T <sub>STG</sub>	Storage Temperature	-55 ~ 150	°C

## Electrical Characteristics T<sub>a</sub>=25°C unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Тур.	Max.	Units
I <sub>CBO</sub>	Collector Cut-off Current	V <sub>CB</sub> =60V, I <sub>E</sub> =0			0.1	μΑ
I <sub>EBO</sub>	Emitter Cut-off Current	$V_{EB}$ =5V, $I_{C}$ =0			0.1	μΑ
h <sub>FE</sub>	DC Current Gain	V <sub>CE</sub> =6V, I <sub>C</sub> =1mA	90	200	600	
V <sub>CE</sub> (sat)	Collector-Emitter Saturation Voltage	I <sub>C</sub> =100mA, I <sub>B</sub> =10mA		0.15	0.3	V
V <sub>BE</sub> (sat)	Base-Emitter Saturation Voltage	I <sub>C</sub> =100mA, I <sub>B</sub> =10mA		0.86	1.0	V
V <sub>BE</sub> (on)	Base-Emitter On Voltage	V <sub>CE</sub> =6V, I <sub>C</sub> =1mA	0.55	0.62	0.65	V
f <sub>T</sub>	Current Gain Bandwidth Product	V <sub>CE</sub> =6V, I <sub>C</sub> =10mA		250		MHz
C <sub>ob</sub>	Output Capacitance	V <sub>CB</sub> =6V, I <sub>E</sub> =0, f=1MHz		3		pF

## **h**<sub>FE</sub> Classification

Classification	0	Y	G	L
h <sub>FE</sub>	90 ~ 180	135 ~ 270	200 ~ 400	300 ~ 600



©2002 Fairchild Semiconductor Corporation

## **Typical Characteristics**




Figure 1. Static Charactersitic




Figure 2. Transfer Characteristic




Figure 3. DC current Gain




Figure 4. Base-Emitter Saturation Voltage Collector-Emitter Saturation Voltage




Figure 5. Output Capacitance






Figure 6. Current Gain Bandwidth Product


©2002 Fairchild Semiconductor Corporation Rev. A2, September 2002

## **Package Dimensions**

## **SOT-23**







Dimensions in Millimeters

#### **TRADEMARKS**

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FACT™	ImpliedDisconnect™	PACMAN™	SPM™
ActiveArray™	FACT Quiet series™	ISOPLANAR™	POP™	Stealth™
Bottomless™	FAST <sup>®</sup>	LittleFET™	Power247™	SuperSOT™-3
CoolFET™	FASTr™	MicroFET™	PowerTrench <sup>®</sup>	SuperSOT™-6
$CROSSVOLT^{TM}$	FRFET™	MicroPak™	QFET™	SuperSOT™-8
DOME™	GlobalOptoisolator™	MICROWIRE™	QS™	SyncFET™
EcoSPARK™	GTO™	MSX™	QT Optoelectronics™	TinyLogic™
E <sup>2</sup> CMOS™	HiSeC™	MSXPro™	Quiet Series™	TruTranslation™
EnSigna™	$I^2C^{TM}$	$OCX^{TM}$	RapidConfigure™	UHC™
Across the board.	Around the world.™	OCXPro™	RapidConnect™	UltraFET <sup>®</sup>
The Power Franci	hise™	OPTOLOGIC <sup>®</sup>	SILENT SWITCHER®	VCX <sup>TM</sup>
Programmable Ad	ctive Droop™	OPTOPLANAR™	SMART START™	

#### **DISCLAIMER**

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## **PRODUCT STATUS DEFINITIONS**

### **Definition of Terms**

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

Go

Home >> Find products >>

## **KSC1623**

NPN Epitaxial Silicon Transistor

#### **Contents**

- Features
- Applications
- Product status/pricing/packaging
- Order Samples

#### **Features**

Complement to KSA812

back to top

### **Applications**

Low Frequency Amplifier & High Frequency OSC.

#### back to top

Product status/pricing/packaging

BUY

Models

Qualification Support

BUY

Datasheet Download this datasheet



e-mail this datasheet



This page Print version

#### **Related Links**

Request samples

How to order products

**Product Change Notices** (PCNs)

Support

Sales support

Quality and reliability

Design center

Product	Product status	Pb-free Status	Pricing*	Package type	Leads	Packing method	Package Marking Convention**
KSC1623GMTF	Full Production	Full Production	\$0.0281	<u>SOT-23</u>	3	TAPE REEL	<u>Line 1:</u> C1G
KSC1623GMTF_NL	Full Production	Full Production	N/A	<u>SOT-23</u>	3	TAPE REEL	<u>Line 1:</u> C1G
KSC1623LMTF	Full Production	Full Production	\$0.0281	SOT-23	3	TAPE REEL	<u>Line 1:</u> C1L

KSC1623OMTF	Full Production	Full Production	\$0.0281	SOT-23	3	TAPE REEL	<u>Line 1:</u> C10
KSC1623YMTF	Full Production	Full Production	\$0.0281	SOT-23	3	TAPE REEL	Line 1: C1Y
KSC1623YMTF_NL	Full Production	Full Production	N/A	SOT-23	3	TAPE REEL	Line 1: C1Y

<sup>\*</sup> Fairchild 1,000 piece Budgetary Pricing

\*\* A sample button will appear if the part is available through Fairchild's on-line samples program. If there is no sample button, please contact a Fairchild distributor to obtain samples



Indicates product with Pb-free second-level interconnect. For more information click here.

Package marking information for product KSC1623 is available. Click here for more information.

## back to top

## Models

Package & leads	Condition	Temperature range Vcc range		Software version	Revision date
		PSPICE			
SOT-23-3	Electrical/Thermal	-55°C to 150°C	0V to 20V	9.2	Jan 15, 2004

## back to top

## **Qualification Support**

Click on a product for detailed qualification data

Product
KSC1623GMTF
KSC1623GMTF_NL
KSC1623LMTF
KSC1623OMTF
KSC1623YMTF

## KSC1623YMTF\_NL

## back to top

## © 2007 Fairchild Semiconductor



Products | Design Center | Support | Company News | Investors | My Fairchild | Contact Us | Site Index | Privacy Policy | Site Terms & Conditions | Standard Terms & Conditions |