

Part Number: C6026A

Revision Level: 1

Date: 11/26/2007

15P 22 7/30 TC SR-PVC PVC

AUDIO CABLE

A. CONSTRUCTION

Conductor:	#22 AWG 7/30 Tinned Copper	0.030" nom.
Insulation:	0.010" Wall Semi-Rigid Polyvinyl Chloride	0.050" nom.
Pairing	30 conductors into 15 pairs @ 2.00" LHL.	0.100" nom.
Cable:	15 pairs @ 5.00" LHL with Mylar wrap.	0.392" nom.
Jacket:	0.032" Wall Polyvinyl Chloride - Gray	0.456" +/- 0.023"
Print Legend:	CAROL (R) 22 AWG -- C6026A -- 75C E111240-8 CM (UL) C (UL) --- AWM STYLE 2464 --- CSA LL69381 CMG -- MADE IN USA (DATE CODE)	

DIAMETERS

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	16.6 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	24.5 pF/ft @ 1kHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	P1=Black, Red	11	P11=Red, Yellow
2	P2= Black, White	12	P12= Red, Brown
3	P3=Black, Green	13	P13=Red, Orange
4	P4=Black, Blue	14	P14=Green, White
5	P5= Black, Yellow	15	P15=Green, Blue
6	P6= Black, Brown		
7	P7=Black, Orange		
8	P8= Red, White		
9	P9=Red, Green		
10	P10=Red, Blue		