






Flanged Spade Terminals



1-800-800-0449



Flanged Spade Terminals 22 to 10 Wire Range



MATERIAL: COPPER

KRIMPTITE®

INSULKRIMP®
(PVC INSULATION)




VERSAKRIMP™

AVIKRIMP®
(NYLON INSULATION)

Wire Range	Stud Size S	Max. Width W	Min. Clearance C	Part Number	Max. Length L	Part Number	Max. Length L	Part Number	Max. Length L	Part Number	Max. Length L	
22 18 0.3-1.0mm ²	1-2 (2) 3-4 (2,6)	.197 (5,0)	.178 (4,5)	—	.502 (12,8)	—	.727 (18,5)	—	.502 (12,8)	—	.727 (18,5)	
		.301 (7,6)	.207 (5,3)	—	.502 (12,8)	AA-2108-04X	.727 (18,5)	AA-3108-04	.502 (12,8)	—	.727 (18,5)	
		.301 (7,6)	.207 (5,3)	—	.556 (14,1)	—	.781 (19,8)	—	.556 (14,1)	—	.781 (19,8)	
	5/6 (3-3,5)	.301 (7,6)	.207 (5,3)	AA-115-06	.556 (14,1)	AA-215-06X	.781 (19,8)	AA-315-06	.556 (14,1)	AA-815-06	.781 (19,8)	
		.335 (8,5)	.235 (5,9)	AA-196-06	.640 (16,2)	AA-296-06X	.865 (21,9)	AA-396-06	.640 (16,2)	AA-896-06	.865 (21,9)	
		.301 (7,6)	.207 (5,3)	—	.556 (14,1)	—	.781 (19,8)	—	.556 (14,1)	—	.781 (19,8)	
	8 (4)	.301 (7,6)	.207 (5,3)	AA-115-08	.556 (14,1)	AA-215-08X	.781 (19,8)	AA-315-08	.556 (14,1)	AA-815-08	.781 (19,8)	
		.335 (8,5)	.235 (5,9)	—	.640 (16,2)	—	.865 (21,9)	AA-396-08	.640 (16,2)	AA-896-08	.865 (21,9)	
		.301 (7,6)	.207 (5,3)	—	.556 (14,1)	—	.781 (19,8)	—	.556 (14,1)	—	.781 (19,8)	
	10 (-)	.301 (7,6)	.207 (5,3)	AA-115-10	.556 (14,1)	AA-215-10X	.781 (19,8)	AA-315-10	.556 (14,1)	AA-815-10	.781 (19,8)	
		.385 (9,8)	.235 (5,9)	AA-193-10	.640 (16,2)	—	.865 (21,9)	—	.640 (16,2)	AA-893-10	.865 (21,9)	
		.301 (7,6)	.209 (5,3)	—	.570 (14,4)	—	.795 (20,2)	BB-316-04	.570 (14,4)	—	.810 (20,6)	
16 14 1.2-2.0mm ²	3-4 (2,6) 5-6 (3-3,5)	.301 (7,6)	.209 (5,3)	—	.570 (14,4)	—	.795 (20,2)	—	.570 (14,4)	—	.810 (20,6)	
		.301 (7,6)	.209 (5,3)	BB-116-06	.570 (14,4)	BB-216-06X	.795 (20,2)	BB-316-06	.570 (14,4)	BB-816-06	.810 (20,6)	
		.301 (7,6)	.209 (5,3)	—	.570 (14,4)	—	.795 (20,2)	BB-3491-08	.570 (14,4)	—	.810 (20,6)	
	8 (4)	.301 (7,6)	.209 (5,3)	BB-116-08	.570 (14,4)	BB-216-08X	.795 (20,2)	BB-316-08	.570 (14,4)	BB-816-08	.810 (20,6)	
		.335 (8,5)	.235 (6,0)	—	.632 (16,0)	—	.857 (21,8)	—	.632 (16,0)	BB-886-08	.872 (22,1)	
		.301 (7,6)	.209 (5,3)	—	.570 (14,4)	—	.795 (20,2)	BB-3491-10	.570 (14,4)	—	.810 (20,6)	
	10 (-)	.301 (7,6)	.209 (5,3)	BB-116-10	.570 (14,4)	BB-216-10X	.795 (20,2)	BB-316-10	.570 (14,4)	BB-816-10	.810 (20,6)	
		.385 (9,8)	.235 (6,0)	BB-183-10	.633 (16,1)	BB-283-10X	.858 (21,8)	BB-383-10	.633 (16,1)	BB-883-10	.873 (22,2)	
		.301 (7,6)	.209 (5,3)	—	.784 (19,9)	C-2104-06X	1.075 (27,3)	C-3104-06	.784 (19,9)	—	1.090 (27,7)	
	12 10 3.0-6.0mm ²	5-6 (3-3,5)	.385 (9,8)	.301 (7,7)	—	.770 (19,6)	C-217-06X	1.061 (27,0)	—	.770 (19,6)	—	1.076 (27,3)
			.330 (8,4)	.305 (7,8)	C-1104-08	.784 (19,9)	C-2104-08X	1.075 (27,3)	—	.784 (19,9)	—	1.090 (27,7)
			.385 (9,8)	.301 (7,7)	C-117-08	.770 (19,6)	C-217-08X	1.061 (27,0)	C-317-08	.770 (19,6)	†C-817-08	1.076 (27,3)
8 (4)		.425 (10,8)	.305 (7,8)	—	.784 (19,9)	C-2101-08X	1.075 (27,3)	—	.784 (19,9)	—	1.090 (27,7)	
		.330 (8,4)	.305 (7,8)	C-1104-10	.784 (19,9)	C-2104-10X	1.075 (27,3)	C-3104-10	.784 (19,9)	—	1.090 (27,7)	
		.385 (9,8)	.301 (7,7)	C-117-10	.770 (19,6)	C-217-10X	1.061 (27,0)	C-317-10	.770 (19,6)	†C-817-10	1.076 (27,3)	

25

Flanged Spade Tongue Terminals 14/12 Wire Range



MATERIAL: COPPER

KRIMPTITE®

VERSAKRIMP™

Wire Range	Stud Size S	Max. Width W	Min. Clearance C	Part Number	Max. Length L	Part Number	Max. Length L
14-12 2.0-3.0mm ²	10 (-)	.425 (10,8)	.370 (9,4)	P-1129-10	.816 (20,7)	—	.816 (20,7)

*Please consult factory for minimum order quantity.

Note: For Terminals on Mylar Tape, add "T" at the end of loose piece part number.

Product Specifications

Wire Range	Barrel Length	Material Thickness Max.	Insulation Color	Max. Wire Insulation Dia.		Circular Mil Area
				Insulkrimp®	Avikrimp®	
22-18 AWG	.175 (4,4)	.032 (0,8)	Red	.145 (3,7)	.140 (3,6)	509-2,600
16-14 AWG	.175 (4,4)	.032 (0,8)	Blue	.175 (4,4)	.170 (4,3)	2,050-5,180
14-12 AWG	.200 (5,1)	.040 (1,0)	Yellow	—	—	3,260-8,230
12-10 AWG	.250 (6,4)	.040 (1,0)	Yellow	.250 (6,4)	.225 (5,7)	5,180-13,100

†For heavier wire insulation the maximum wire insulation diameter can be expanded to .255 (6,5) by adding "X" to the end of the part number.