

BLF052-6V-P	BLB101-6V-P	BLB102-6V-P	BLS101-6V-P
-------------	-------------	-------------	-------------

Part No.	Emitting Color + Material	Wave-length (nm)	Lens Type	Iv (mcd)		Viewing Angle	Dimension
				V=12V, Min.	V=6V V=24 Typ.		

BLF052SURC-E-6V-P	InGaAlP	640	water clear	1000	2000	45°	5mm Flange Base
BLF052SURC-E-12V-P	InGaAlP	640	water clear	1000	2000	45°	
BLF052SURC-E-24V-P	InGaAlP	640	water clear	1000	2000	45°	
BLF052MGC-6V-P	InGaAlP	565	water clear	400	1000	45°	
BLF052MGC-12V-P	InGaAlP	565	water clear	400	1000	45°	
BLF052MGC-24V-P	InGaAlP	565	water clear	400	1000	45°	
BLF052SYC-6V-P	InGaAlP	590	water clear	400	1000	45°	
BLF052SYC-12V-P	InGaAlP	590	water clear	400	1000	45°	
BLF052SYC-24V-P	InGaAlP	590	water clear	400	1000	45°	

BLB101SURC-E-6V-P	InGaAlP	640	water clear	1000	2500	20°	10mm Bayonet Base
BLB101SURC-E-12V-P	InGaAlP	640	water clear	1000	2500	20°	
BLB101SURC-E-24V-P	InGaAlP	640	water clear	1000	2500	20°	
BLB101MGC-6V-P	InGaAlP	565	water clear	500	1000	20°	
BLB101MGC-12V-P	InGaAlP	565	water clear	500	1000	20°	
BLB101MGC-24V-P	InGaAlP	565	water clear	500	1000	20°	
BLB101SYC-6V-P	InGaAlP	590	water clear	700	1500	20°	
BLB101SYC-12V-P	InGaAlP	590	water clear	700	1500	20°	
BLB101SYC-24V-P	InGaAlP	590	water clear	700	1500	20°	

BLB102SURC-E-6V-P	InGaAlP	640	water clear	1000	2500	40°	10mm Bayonet Base
BLB102SURC-E-12V-P	InGaAlP	640	water clear	1000	2500	40°	
BLB102SURC-E-24V-P	InGaAlP	640	water clear	1000	2500	40°	
BLB102MGC-6V-P	InGaAlP	565	water clear	500	1000	40°	
BLB102MGC-12V-P	InGaAlP	565	water clear	500	1000	40°	
BLB102MGC-24V-P	InGaAlP	565	water clear	500	1000	40°	
BLB102SYC-6V-P	InGaAlP	590	water clear	700	1500	40°	
BLB102SYC-12V-P	InGaAlP	590	water clear	700	1500	40°	
BLB102SYC-24V-P	InGaAlP	590	water clear	700	1500	40°	

BLS101SURC-E-6V-P	InGaAlP	640	water clear	1000	2500	20°	10mm Screw Base
BLS101SURC-E-12V-P	InGaAlP	640	water clear	1000	2500	20°	
BLS101SURC-E-24V-P	InGaAlP	640	water clear	1000	2500	20°	
BLS101MGC-6V-P	InGaAlP	565	water clear	500	1000	20°	
BLS101MGC-12V-P	InGaAlP	565	water clear	500	1000	20°	
BLS101MGC-24V-P	InGaAlP	565	water clear	500	1000	20°	
BLS101SYC-6V-P	InGaAlP	590	water clear	700	1500	20°	
BLS101SYC-12V-P	InGaAlP	590	water clear	700	1500	20°	
BLS101SYC-24V-P	InGaAlP	590	water clear	700	1500	20°	

NOTES :

1. All dimensions are in millimeters (inches)
2. Tolerance is ±0.25mm(0.01") unless otherwise noted.