




## Screw Mount D-Clip

### Features and Benefits

Screwed D-clips are available in 3 sizes and guarantee time and cost saving by simply pressing the cable into the holder. The flexible grip means that later removal or replacement of cables and pipes is possible. 3 different bore diameters for fixing the holder are available



The clip is held in place by a screw and the bundled cable or pipe is guided securely.



D-Clip

### Material Data

Material	<b>Polyacetal (POM)</b>
Operating Temperature	<b>-40 °C to +90 °C Continuous, (+110 °C for 500 h)</b>
Flammability	<b>UL94 HB</b>



### Technical Table

Article-No.	Type	Length (L)	Length (L2)	Width (W)	Wall (WT)	Fixing Hole Ø (FH)	Bundle Ø max.	Material	Colour
211-70000	<b>4D10</b>	17.0	8.0	15.0	2.0	4.0	10.0	POM	Black (BK)
211-70001	<b>4D15</b>	25.0	10.0	15.0	2.0	4.0	15.0	POM	Black (BK)
211-70002	<b>4D20</b>	28.0	10.0	15.0	2.5	4.0	20.0	POM	Black (BK)
211-70100	<b>6D10</b>	17.0	8.0	15.0	2.0	6.0	10.0	POM	Black (BK)
211-70101	<b>6D15</b>	25.0	10.0	15.0	2.0	6.0	15.0	POM	Black (BK)
211-70104	<b>6D20</b>	28.0	10.0	15.0	2.5	6.0	20.0	POM	Black (BK)
211-70200	<b>8D10</b>	17.0	8.0	15.0	2.0	8.0	10.0	POM	Black (BK)
211-70203	<b>8D15</b>	25.0	10.0	15.0	2.0	8.0	15.0	POM	Black (BK)
211-70204	<b>8D20</b>	28.0	10.0	15.0	2.5	8.0	20.0	POM	Black (BK)

All dimensions in mm. Subject to technical changes.