BGA Heat Sink (High Aspect Ratio Ext.) **Straight Fin**





ATS Part#:

Description:

ATS017017017-SF-5P

17.00 x 17.00 x 17.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Straight Fin

Heat Sink Type: Straight Fin Heat Sink Attachment: Equivalent Part Number: N/A

superGRIP

*Image above is for illustration purpose only.

Features & Benefits

- · High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- Features a low profile, slant fin array that offers many of the performance benefits of maxiFLOW™ at a great value .
- . Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option ٠

Thermal Performance

| AIR VELOCITY | | @200 LFM 1.0 M/S | @300 LFM 1.5 M/S | @400 LFM 2.0 M/S | @500 LFM 2.5 M/S | @600 LFM 3.0 M/S | @700 LFM 3.5 M/S | @800 LFM 4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 8.68 °C/W | 6.7 °C/W | 5.7 °C/W | 5.1 °C/W | 4.7 °C/W | 4.4 °C/W | 4.1 °C/W |
| | Ducted Flow | 5.5 | 4.6 | 4.1 | 3.8 | 3.5 | 3.3 | 3.2 |

Product Detail

| Schematic Image | Dimension A | Dimension B | Dimension C | Dimension D | тім | Finish |
|---|---|---|--|--|--------------------|----------------|
| (mark) | 17.00 mm | 17.00 mm | 17.00 mm | 17 mm | N/A | BLACK-ANODIZED |
| Image above is for illustration purpose only. | Dimension Dimension Thermal papplication ATS resension ATS resension ATS certifier | n D is fin tip to fin tip performance data are n. rves the right to upd nce. | e provided for refere ate or change its pro k assembly is RoHS | m of the base to the nce only. Actual perf ducts without notice 6-6 and REACH com ble. | formanc to impr | e may vary by |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA