



NOTES:

1. FOR USE WITH BOEING BMS13-65 OK & ADAMS RUSSELL FC48Z CABLE.
2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
3. FOR CRIMPING USE KTH-2229.
4. INTERFACE PER MIL-STD-348, FIG. 304-2.
5. CENTER CONTACT (1-7311-1MA9) SUPPLIED UNASSEMBLED.
6. MARK PACKAGE: KINGS 1203-21-9 (DATE CODE)
7. MATERIALS:
 INSULATOR: TEFLON, ASTM D1710
 CENTER CONTACT: BER. COP., ASTM B196
 K-GRIP SLEEVE: COM. BRONZE, ASTM B135
 ALL OTHER PARTS: BRASS B16
8. FINISHES:
 CENTER CONTACT: .000050 MIN GOLD PLATE PER ASTM B488 OVER .000050 MIN NICKEL PER ASM-QQ-N-290 (RoHS)
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PER ASM-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
9. ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 50 OHMS
 VOLTAGE RATING: 500 VRMS
 FREQUENCY RANGE: DC TO 11 GHz
10. WEIGHT: 46.9 GRAMS

1203-21-9

REVISIONS	
ISSUE	CHANGES
0	ER 35891 KVH 11/04/94
B	REVISED PER DMF304 & ER34618 KPL 08/29/11

CUSTOMER SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE	4:1		
APPROX SURFACE AREA			
WAS:	E-18478		
CAGE CODE:	91836		
REF:	LOCKHEED		
JACK, N			
DRAWN	MJB	DATE	08/09/94
DESIGN	CT	DATE	08/09/94
APPR.	CT	DATE	11/09/94

WINCHESTER ELECTRONICS
 Winchester Electronics Corporation
 62 Barnes Industrial Road North
 Wallingford, Connecticut 06492

1203-21-9