




FCS-3054 2022 22: 1

## Fixed Dome Network Camera, 3-Megapixel, PoE 802.3af



### Key Features

- 20 200000 22 Micro SDHC/SDXC 22 22
- 3-20000 20000
- Vandal-proof IK08-rated housing
- 22: H.264/MJPEG
- Power support: PoE (IEEE 802.3af)
- 22 64-22 20000 2000 22(OneSecure App 22)



## System Specifications

### Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet

IEEE 802.3u 100-BASE-TX, Fast Ethernet

IEEE 802.3af Power over Ethernet (PoE)

IEEE 802.1X Network Access Control

TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour

### Image Sensor:

3-Megapixel 1/3.2" Progressive Scan CMOS

### Connectors and Cabling:

1 x RJ-45 10/100 Mbps PoE port

### Modularity:

1 x MicroSDHC/ MicroSDXC card slot

### Button:

Reset Button

### Indicator:

Power

### Lens:

Fixed focal, Fixed iris, Fixed focus, f2.93mm , F2.0

### Shutter Time:

1/5 ~ 1/10,000 sec

### Angle of View:

83.3°

### Pan/Tilt/Zoom:

Digital Zoom to very high detail available on Software

### Video Compression:

H.264 / MJPEG

### Resolution:

3M(2048 x 1536)

### Video Format:

RAW

### Audio Compression:

G.711

### Power:

Power Consumption: PoE Class 1 (IEEE802.3af) / 2.91W

Power Input: 802.3af PoE

## Features

### General:

Backup: MicroSDHC /MicroSDXC card slot for local storage

### Video:

Image Setting: - Adjustable image size, quality and bit rate

- Configurable brightness, sharpness, contrast, saturation, white balance and exposure

- AGC/AWB/AES

- Back Light Compensation (BLC)

- 2D Noise Reduction (2DNR)

Streaming: Up to 2 video streams

## Performance

**Data Transfer Rate:**

10/100Mbps

**Storage Capacity:**

SD/MicroSD memory card of up to 64GB

**Frame Rate:**

15 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 240

**Minimum illumination:**

Color: 0.1 lux at F2.0

## Environment

**Temperature (°C):**

Operating: -10°C ~ 50°C

**Humidity (Non-condensing):**

Operating: 10% ~ 85%

## Physical Specifications

**Dimensions (W x D x H mm):**

110 x 58 x 110

**Weight (g):**

202 g

**Enclosure:**

Vandal Resistant IK08-reted

## Others

**Approval and Compliance:**


CE, FCC, IK08

**Deployment:**

Wall/Ceiling Mount

**Operation Systems:**

Microsoft Windows 8/7/Vista/XP



---

## Order Information

FCS-3054

---

## Package Contents

FCS-3054  
Mounting Kit  
Screw Kit  
Quick Installation Guide  
Resource CD (User Manual, Utility, QIG)

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.