

*New Jersey Semi-Conductor Products, Inc.*

20 STERN AVE.  
 SPRINGFIELD, NEW JERSEY 07081  
 U.S.A.

TELEPHONE: (201) 376-2922  
 (212) 227-6005  
 TELFX: 13-8720

**1N3062 • 1N3063 • 1N3064 • 1N4305 • 1N4454**  
**ULTRA FAST LOW CAPACITANCE**  
 DIFFUSED SILICON PLANAR\* DIODES

- C ... 2.0 pF @  $V_R = 0$ ,  $f = 1.0$  MHz
- $t_{rr}$  ... 4.0 ns @  $I_f = 10$  mA,  $R_f = 10$  mA,  $V_f = 1.0$  V
- BV ... 75 V (MIN)

**ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ ) (Note 1)**

Maximum Temperatures	1N3062 1N3063	1N3064	1N4454	1N4305
Storage Temperature	-65°C to +200°C	-65°C to +175°C	-65°C to +175°C	-65°C to +200°C
Operating Temperature	-65°C to +175°C	-65°C to +150°C	-65°C to +150°C	-65°C to +150°C
<b>Maximum Power Dissipation</b>				
Total Dissipation	250 mW	250 mW	500 mW	500 mW
Linear Derating Factor	1.67 mW/°C	2.0 mW/°C	4.0 mW/°C	2.85 mW/°C
<b>Maximum Voltages and Currents</b>				
WIV Working Inverse Voltage	50 V	50 V	40 V	75 V
$I_O$ Average Rectified Current	75 mA	75 mA	200 mA	
$I_F$ Forward Current Steady State dc	115 mA	115 mA	400 mA	
$i_f$ Recurrent Peak Forward Current	225 mA	225 mA	600 mA	
$i_f$ (surge) Peak Forward Surge Current				
Pulse Width = 1.0 s	500 mA	500 mA	1.0 A	
Pulse Width = 1.0 $\mu$ s	2.0 A	2.0 A	4.0 A	

**ELECTRICAL CHARACTERISTICS ( $25^\circ\text{C}$  Ambient Temperature unless otherwise noted)**

SYMBOL	CHARACTERISTIC	MIN.	MAX.	UNITS	TEST CONDITIONS					
$V_F$	Forward Voltage	1N3062 1N3063 1N4305	0.700	1.0	V	$I_F = 20$ mA				
				0.850	V	$I_F = 10$ mA				
				0.610	V	$I_F = 2.0$ mA				
		1N3064 1N4454	0.550	0.650	V	$I_F = 1.0$ mA				
				0.505	V	$I_F = 250$ $\mu$ A				
				1.0	V	$I_F = 10$ mA				
$I_R$	Reverse Current		0.1	$\mu$ A	$V_R = 50$ V					
$I_R$	Reverse Current		100	$\mu$ A	$V_R = 50$ V, $T_A = 150^\circ\text{C}$					
BV	Breakdown Voltage	75		V	$I_R = 5.0$ $\mu$ A					
$t_{rr}$	Reverse Recovery Time	1N4305	2.0	ns		$I_f = 10$ mA, $V_f = 6.0$ V, $R_L = 100$ $\Omega$				
							1N3062 1N3063 1N3064 1N4454 1N4305	4.0	ns	
		1N3062 1N3063 1N3064 1N4454 1N4305	1.0	pF	$V_R = 0$ , $f = 1.0$ MHz					
						2.0				
							45	%	$f = 1.0$ MHz	
1.8	mV/°C									
		3.0	mV/°C							
				1N3062 1N3063 1N3064 1N4454 1N4305						