



Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

**2SD880-Q
2SD880-Y
2SD880-GR**

Features

- Halogen free available upon request by adding suffix "-HF"
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Power amplifier applications
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Mounting Torque: 5 in-lbs Maximum

Symbol	Rating	Rating	Unit
V _{CEO}	Collector-Emitter Voltage	60	V
V _{CBO}	Collector-Base Voltage	60	V
V _{EBO}	Emitter-Base Voltage	7	V
I _C	Collector Current	3	A
P _C	Collector power dissipation	1.5	W
T _J	Junction Temperature	-55 to +150	°C
T _{STG}	Storage Temperature	-55 to +150	°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Type	Max	Units
OFF CHARACTERISTICS					
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage (I _C =50mA, I _B =0)	60	---	---	Vdc
V _{(BR)CBO}	Collector-Base Breakdown Voltage (I _C =100uA, I _E =0)	60	---	---	Vdc
V _{(BR)EBO}	Emitter-Base Breakdown Voltage (I _E =100uA, I _C =0)	7	---	---	Vdc
I _{CBO}	Collector-Base Cutoff Current (V _{CB} =60Vdc, I _E =0)	---	---	100	uA
I _{EBO}	Emitter-Base Cutoff Current (V _{EB} =7Vdc, I _C =0)	---	---	100	uA

ON CHARACTERISTICS

h _{FE}	Forward Current Transfer ratio (I _C =500mA, V _{CE} =5Vdc)	60	---	300	---
V _{CE(sat)}	Collector-Emitter Saturation Voltage (I _C =3A, I _B =300mA)	---	---	1	Vdc
V _{BE}	Base-Emitter Voltage (I _C =0.5A, V _{CE} =5Vdc)	---	---	1	Vdc
f _T	Transistor Frequency (I _C =500mA, V _{CE} =5Vdc)	---	3	---	MHz
C _{ob}	Collector Output Capacitance (V _{CB} =10Vdc, I _E =0, f=1MHz)	---	70	---	pF
t _{on}	Turn on time	---	0.8	---	us
t _s	Storage time	---	1.5	---	us
t _f	Fall time	---	0.8	---	us


Classification Of h_{FE}

Rank	Q	Y	GR
Range	60-120	100-200	150-300

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

**NPN Silicon
Power Transistors**

TO-220



DIM	DIMENSIONS				NOTE
	INCHES		MM		
A	.560	.625	14.22	15.88	
B	.380	.420	9.65	10.67	
C	.140	.190	3.56	4.82	
D	.020	.045	0.51	1.14	
F	.139	.161	3.53	4.09	∅
G	.190	.110	2.29	2.79	
H	---	.250	---	6.35	
J	.012	.025	0.30	0.64	
K	.500	.580	12.70	14.73	
L	.045	.060	1.14	1.52	
N	.190	.210	4.83	5.33	
Q	.100	.135	2.54	3.43	
R	.080	.115	2.04	2.92	
S	.045	.055	1.14	1.39	
T	.230	.270	5.84	6.86	
U	---	.050	---	1.27	
V	.045	---	1.15	---	



Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-BP	Bulk; 1 Kpcs/Box

Note : Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com