

QT-Brightek Lamp Series

5mm IR Lamp LED

Part No.: QBED8340

Product: QBED8340	Date: March 27, 2014	Page 1 of 7
	Version# 1.0	

Table of Contents:

Introduction	3
Electrical / Optical Characteristic (Ta=25 °C)	4
Absolute Maximum Rating	4
Characteristic Curves.....	5
Packing	6
Labeling	6
Ordering Information	6
Revision History	7
Disclaimer	7

Introduction

Feature:

- Water clear lens
- Package in bulk
- High radiant intensity
- Peak wavelength $\lambda_p=850\text{nm}$
- 40 degree viewing angle

Description:


This device is spectrally match with phototransistor, photodiode, and infrared receiver module

Application:

- Free air transmission system
- Optoelectronic switch
- Infrared applied system
- Smoke Detector

Certification & Compliance:

- TS16949
- ISO9001
- RoHS Compliant

**Dimension:**

- 1、 Anode
- 2、 Cathode

Units: mm / tolerance = +/-0.2mm

Electrical / Optical Characteristic (Ta=25 °C)

Parameter	Symbol	Test Condition	Output			Units
			Min.	Typ.	Max.	
Forward Voltage	V_F	$I_F=50\text{mA}$	-	1.4	1.60	V
Pulse Forward Voltage	V_{FP}	$I_{FP}=700\text{mA}, t_p=10\mu\text{s}$	-	-	3.50	
Reverse Current	I_R	$V_R=5\text{V}$	-	-	10	μA
Radiant Intensity	I_E	$I_F=50\text{mA}$	30	45	-	mW/sr
		$I_F=100\text{mA}, t=20\text{ms}$	60	80	-	
Peak Radiation Wavelength	λ_P	$I_F=50\text{mA}$	-	850	-	nm
Half Spectrum Width	$\Delta\lambda$	$I_F=50\text{mA}$	-	40	-	nm
Viewing Angle	$2\Theta_{1/2}$	$I_F=50\text{mA}$	-	40	-	deg
Switch Time	t_r/t_f	$I_{FP}=100\text{mA}, f=1\text{KHz}, t_p/T=1\%$	-	25/15	-	ns

Absolute Maximum Rating

Parameter	Symbol	Rating	Units
Continuous Forward Current	I_F	100	mA
Peak Forward Current	I_{FP}	1	A
Reverse Voltage	V_R	5	V
Power Dissipation at (or below) 25 °C Free Air Temperature	P_d	120	mW
Operating Temperature	T_{opr}	-25 ~ +85	°C
Storage Temperature	T_{stg}	-40 ~ +100	°C

Characteristic Curves




Fig.1 Forward Current vs. Forward Voltage




Fig.2 Radiant Intensity vs. Forward Current




Fig.3 Forward Current vs. Ambient Temperature




Fig.4 Relative Radiant Intensity vs. Ambient Temperature




Fig.5 Relative Radiant Intensity vs. Wavelength




Fig.6 Relative Radiant Intensity vs. Angular Displacement

Packing

500pcs per bag

LabelingPart No: _____Customer P/N: _____Item: _____Q'ty: _____Vf: _____Iv: _____WI: _____Date: _____**Made in China****Ordering Information**

Part #	Orderable Part #	Spec Range	Quantity per bag
QBED8340	QBED8340	I _e =80mW mW/sr. @ I _F =100mA, t=20ms / λ _P =850nm typ.	500pcs

Revision History

Description:	Revision #	Revision Date
New Release of QBED8340	V1.0	03/27/2014

Disclaimer

QT-BRIGHTTEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. QT-BRIGHTTEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

Life Support Policy

QT-BRIGHTTEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of QT-BRIGHTTEK. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.