



IGP-0801 [?] [?] [?]: 1

8-Port Gigabit PoE Industrial Switch, 4 PoE Outputs, 802.3at PoE+, 126W, -40°C to 75°C

The LevelOne IGP-0801 is 10/100/1000M industrial 8 port high power POE switch is equipped with 4 port 30Watts PSE. It is designed for 48-56VDC input sources, especially for IP surveillance, traffic monitoring and for a broad range of applications. It can be used as a stand-alone device for buses, trucks, and other vehicles for Surveillance purposes. It is being rigorously tested for your Security, Transportation and Telco application.

Key Features

- PoE ports can support the IEEE 802.3at standard and power up 30W devices
- 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- Provides DIN-rail, wall or desktop mounting
- IP30 metal case
- Redundant power inputs with Terminal Block
- [?] [?]: -40°C ~ 75°C



System Specifications

Standards & Protocols:

IEEE 802.3 10Base-T Ethernet
 IEEE 802.3u 100Base-TX Fast Ethernet
 IEEE 802.3ab 1000Base-T Gigabit Ethernet
 IEEE 802.3z 1000Base-X Gigabit Ethernet
 IEEE802.3x Flow Control and Back Pressure,
 IEEE802.3af for POE
 IEEE802.3at for POE+

Buffer Memory:

1M

Connectors and Cabling:

8 x RJ-45 10/100/1000 BaseT(X) auto negotiation,
 4 x Giga POE+ 802.3at/af PSE port
 Auto MDI/MDI-X function, Full/Half duplex

Indicator:

Per Unit: Power
 Per Port: Ethernet Link, PoE Status

**Transmission Method:**

Store & Forward

Power Input:

Redundant Dual DC 44V-56V Power Input

POE input 44-56VDC

Power Consumption:

5.76W@48 VDC full load, Without POE

Features**General:**

1000Base-T, 100 Base-Tx, 10Base-T Ethernet

4Port PoE Output

PoE:

POE power per port 30watts. Maximum 36Watts

Maximum total power 126Watts with 56VDC input, Supports IEEE802.3af/at

Ease of Use:

Plug & Play

Performance**Backplane (Gbps):**

16G bps

MAC Address Table:

8K

Packet Forwarding Rate:

1488000 bps

Jumbo Frame (K):

9K Bytes

Environment**Power Saving:**

Green Ethernet

Temperature (°C):

-40°C ~ 75°C

Humidity (Non-condensing):

5% to 95%

Physical Specifications**Dimensions (W x D x H mm):**

142 x 105 x 36.2

Weight (g):

525

Reliability**MTBF:**

510,304 hrs (MIL-HDBK-217F) at 25°C

Order Information

IGP-0801

Package Contents

IGP-0801

Power Terminal Block

Mounting Kit

User Manual

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.