



- NOTES:
1. ALL DIMENSIONS IN MM
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. TERM. NOS. FOR REFERENCE ONLY.
  - ▲ 4. CONTACT RATING: 0.1A MAX. @ 28VDC
  5. CONTACT MATERIAL: GOLD
  6. ELECTRICAL LIFE: 200,000 Typical
  7. OPERATING LIFE: 200,000 CYCLES TYP.
  8. CONTACT RESISTANCE:  
100 MILLI-OHM INITIAL TYP. MAX.
  9. DIELECTRIC STRENGTH:  
1000 VAC FOR 1 MINUTE
  10. TRAVEL TO MAKE: 2.20mm ± 0.2
  11. 2011/65/EU (ROHS) COMPLIANT
  12. ▲ DENOTES CRITICAL PARAMETER
  - ▲ 13. LED COLOR: NO LED



E	22342	UPDATED CONTACT RATING	9/12/16	MJR
D	19703	UPDATE DRAWING	02/23/11	BMA
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE ULP12OAP1RSSCL1NILNIL				
SCALE 3:2	DATE 6/27/2007	DR TN	DWG B800012	REV E

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED