



ADAM PART NUMBER	A	B
2FB-XX-M-ST-A500	.470 [11.95]	.394 [10.00]
2FB-XX-M-ST-A575	.943 [23.95]	.866 [22.00]
2FB-XX-M-ST-A650	1.415 [35.95]	1.339 [34.00]
2FB-XX-M-ST-A725	1.888 [47.95]	1.811 [46.00]
2FB-XX-M-ST-A800	2.360 [59.95]	2.283 [58.00]
2FB-XX-M-ST-B500	2.833 [72.56]	2.756 [70.00]
2FB-XX-M-ST-B575	3.305 [83.95]	3.228 [82.00]
2FB-XX-M-ST-B650	3.778 [95.95]	3.701 [94.00]
2FB-XX-M-ST-B725		
2FB-XX-M-ST-B800		
2FB-XX-M-ST-C500		
2FB-XX-M-ST-C575		
2FB-XX-M-ST-C650		
2FB-XX-M-ST-C725		
2FB-XX-M-ST-C800		

DETAIL Y

SPECIFICATIONS:
 Material: Insulator: Hi Temp Plastic, rated UL 94V-0
 Insulator color: Gray
 Contacts: Brass
 Plating: Gold over Nickel underplate on contact area, Tin over Copper underplate on PCB tails
 Electrical: Current rating: 1 Amps max
 Contact resistance: 30 mohms max
 Insulation resistance: 1000 Mohms min @ 500 VDC
 Dielectric withstanding voltage: 1000 VAC for 1 minute
 Operating temperature: -65°C to +125°C
 Environmental: Lead free, RoHS compliant.
 Recommended soldering temp: 260°C for 5 sec.



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]	
TOLERANCES: EXCEPT AS NOTED	HOLDERS
INCHES	HOLDERS
X ± .10	± .10
.XX ± .020	∅XX ± .015
.XXX ± .015	∅XXX ± .010
APPROVALS	DATE
DRAWN	DY
CHECKED	
APPROVED	
	12/10/09

ADAM TECH
 909 Railway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710
 TITLE: .079 [2.00] FUTURE BUS, MALE, SINGAL,
 4 ROWS, DIP TYPE

SIZE	PART NO.	REV.
X	2FB-XX-M-ST-XXXX	
REF: S00038T	SCALE: NTS	SHEET 1 OF 1