


Features

- Diffused Junction
- Low Leakage
- Low Cost
- High Surge Current Capability
- Die Size 184 mil HEX



Mechanical Data

- Case: Protected with Silicon Rubber
- Terminal: Slug, Cu with Ag Plated
- Polarity: Indicated by Large Slug On Cathode Side
- Mounting Position: Any

| C35 | | |
|----------------------|------|------|
| Dim | Min | Max |
| A | — | 6.19 |
| B | — | 5.46 |
| C | 0.75 | — |
| D | 1.0 | — |
| E | — | 2.2 |
| All Dimensions in mm | | |

Maximum Ratings and Electrical Characteristics @ $T_A=25^\circ\text{C}$ unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

| Characteristic | Symbol | C35A | C35B | C35D | C35G | C35J | C35K | C35M | Unit |
|---|-----------------|-------------|------|------|------|------|------|------|------------------|
| Peak Repetitive Reverse Voltage | V_{RRM} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| Working Peak Reverse Voltage | V_{RWM} | | | | | | | | |
| DC Blocking Voltage | V_R | | | | | | | | |
| RMS Reverse Voltage | $V_{R(RMS)}$ | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V |
| Average Rectified Output Current @ $T_C = 150^\circ\text{C}$ | I_O | 35 | | | | | | | A |
| Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method) | I_{FSM} | 400 | | | | | | | A |
| Forward Voltage @ $I_F = 80\text{A}$ | V_{FM} | 1.08 | | | | | | | V |
| Peak Reverse Current At Rated DC Blocking Voltage @ $T_A = 25^\circ\text{C}$ | I_{RM} | 3.0 | | | | | | | μA |
| Typical Thermal Resistance Junction to Ambient | $R_{\theta JA}$ | 26 | | | | | | | K/W |
| Operating and Storage Temperature Range | T_J, T_{STG} | -40 to +150 | | | | | | | $^\circ\text{C}$ |

*Glass passivated forms are available upon request

ORDERING INFORMATION

| Product No. | Package Type | Shipping Quantity |
|-------------|--------------|-------------------|
| C35A | 6.2mm Cell | 5000 Units/Box |
| C35B | 6.2mm Cell | 5000 Units/Box |
| C35D | 6.2mm Cell | 5000 Units/Box |
| C35G | 6.2mm Cell | 5000 Units/Box |
| C35J | 6.2mm Cell | 5000 Units/Box |
| C35K | 6.2mm Cell | 5000 Units/Box |
| C35M | 6.2mm Cell | 5000 Units/Box |

Shipping quantity given is for minimum packing quantity only. For minimum order quantity, please consult the Sales Department.

Won-Top Electronics Co., Ltd (WTE) has checked all information carefully and believes it to be correct and accurate. However, WTE cannot assume any responsibility for inaccuracies. Furthermore, this information does not give the purchaser of semiconductor devices any license under patent rights to manufacturer. WTE reserves the right to change any or all information herein without further notice.

WARNING: DO NOT USE IN LIFE SUPPORT EQUIPMENT. WTE power semiconductor products are not authorized for use as critical components in life support devices or systems without the express written approval.

Won-Top Electronics Co., Ltd.

No. 44 Yu Kang North 3rd Road, Chine Chen Dist., Kaohsiung, Taiwan

Phone: 886-7-822-5408 or 886-7-822-5410

Fax: 886-7-822-5417

Email: sales@wontop.com

Internet: <http://www.wontop.com>

We power your everyday.