

Vishay Semiconductors


ESD Protection Diode

Features

- Transient protection for data lines as per IEC 61000-4-2 (ESD) 15 kV (air) 8 kV (contact) IEC 61000-4-5 (Lightning) see I_{PPM} below
- Space saving LiLiPut package

Mechanical Data

Case: LLP75-3B Plastic Package Molding Compound Flammability Rating: UL 94 V-0



Terminals: High temperature soldering guaranteed: 260 °C/10 sec. at terminals **Weight:** 5 mg

Parts Table

Part Ordering code		Marking	Remarks	
GSOT05C-HT3	GSOT05C-HT3-GS08	05	Tape and Reel	

Absolute Maximum Ratings

Ratings at 25 °C, ambient temperature unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Peak power dissipation ¹⁾	8/20 μs pulse	P _{PK}	300	W
Forward surge current	8.3 ms single half sine-wave	I _{FSM}	7	А

 $^{1)}$ Non-repetitive current pulse and derated above T_{A} = 25 $^{\circ}C$

Thermal Characteristics

Ratings at 25 °C, ambient temperature unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Operation and storage		T _{stg} , T _J	- 55 to + 150	°C
temperature range				

Electrical Characteristics

Part Number	Device Marking Code	Rated Stand-off Voltage	Minimum Breakdown Voltage	Clam	mum iping age	Maximum Pulse Peak Current	Maximum Leakage Current	Maximum Capacitance
			@ 1 mA	@ I _P = 1 A	@ I _P = 5 A	$t_p = 8/20 \ \mu s$	@ V _{WM}	@ 0 V, 1 MHz
		V _{WM}	V _{BR}	V	С	I _{PPM}	I _D	С
		V	V	V		А	μA	pF
GSOT05C- HT3	05	5.0	6.0	9.8	12.5	17	100	400

GSOT05C - HT3



Vishay Semiconductors

Typical Characteristics ($T_{amb} = 25 \text{ °C}$ unless otherwise specified)





Figure 1. Non -Repetitive Peak Pulse Power vs. Pulse Time







Figure 3. Power Derating



GSOT05C - HT3

Vishay Semiconductors

Package Dimensions in mm



GSOT05C - HT3

Vishay Semiconductors



Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

- 1. Meet all present and future national and international statutory requirements.
- 2. Regularly and continuously improve the performance of our products, processes, distribution and operatingsystems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

- 1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
- 2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
- 3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423 This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.