





# G11 DecorLED™, 25mm Edison Screw Based Lamps

Packages	Replaces Incandescent # (Application Specific)	Part Number	Input Voltage	Power (Watts) typ	Intensity per LED I <sub>v</sub> (mcd) typ	λ <sub>D</sub> (nm)	View Angle 2θ <sub>1/2</sub>	Special Features
660nm Ultra Red GaAIAs/GaAIAs		DEC-G11-0UR-014V	12/14V	1.0 to 1.7	760	660	270°	Contact Polarity V = DC only A = AC only
		DEC-G11-0UR-024V	24V					
		DEC-G11-0UR-120A	120VAC					
		DEC-G11-0UR-240A	240VAC					
633nm Super Red InGaIP		DEC-G11-0ER-014V	12/14V	1.0 to 1.7	1750	633	270°	Contact Polarity V = DC only A = AC only
		DEC-G11-0ER-024V	24V					
		DEC-G11-0ER-120A	120VAC					
		DEC-G11-0ER-240A	240VAC					
612nm Super Orange InGaIP		DEC-G11-0UO-014V	12/14V	1.0 to 1.7	1400	612	270°	Contact Polarity V = DC only A = AC only
		DEC-G11-0UO-024V	24V					
		DEC-G11-0UO-120A	120VAC					
		DEC-G11-0UO-240A	240VAC					
595nm Super Yellow InGaIP		DEC-G11-0UY-014V	12/14V	1.0 to 1.7	1280	595	270°	Contact Polarity V = DC only A = AC only
		DEC-G11-0UY-024V	24V					
		DEC-G11-0UY-120A	120VAC					
		DEC-G11-0UY-240A	240VAC					
8000K Cool White SiC/GaN		DEC-G11-0CW-014V	12/14V	1.0 to 1.7	1100	8000K	270°	Contact Polarity V = DC only A = AC only
		DEC-G11-0CW-024V	24V					
		DEC-G11-0CW-120A	120VAC					
		DEC-G11-0CW-240A	240VAC					
570nm Lime Green InGaIP		DEC-G11-0UG-014V	12/14V	1.0 to 1.7	400	570	270°	Contact Polarity V = DC only A = AC only
		DEC-G11-0UG-024V	24V					
		DEC-G11-0UG-120A	120VAC					
		DEC-G11-0UG-240A	240VAC					
525nm Aqua Green SiC/GaN		DEC-G11-0AG-014V	12/14V	1.0 to 1.7	4400	525	270°	Contact Polarity V = DC only A = AC only
		DEC-G11-0AG-024V	24V					
		DEC-G11-0AG-120A	120VAC					
		DEC-G11-0AG-240A	240VAC					
505nm Blue Green SiC/GaN		DEC-G11-0BG-014V	12/14V	1.0 to 1.7	2000	505	270°	Contact Polarity V = DC only A = AC only
		DEC-G11-0BG-024V	24V					
		DEC-G11-0BG-120A	120VAC					
		DEC-G11-0BG-240A	240VAC					
470nm Super Blue SiC/GaN		DEC-G11-0PB-014V	12/14V	1.0 to 1.7	1300	470	270°	Contact Polarity V = DC only A = AC only
		DEC-G11-0PB-024V	24V					
		DEC-G11-0PB-120A	120VAC					
		DEC-G11-0PB-240A	240VAC					


### Dimensions




### Options



DEC-G11T  
Tinted



DEC-G11F  
Frosted White



DEC-G11C  
Frosted Colored

Log # 123R Rev 12-2000